## MAGNUM STANDARD 50W I CL.WITH SOCKET SCHUKO

**DETAILED CARD** 





Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polypropylene (PP). Anti-glare diffuser made of polycarbonate (PC) transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

#### APPLICATION

The family of durable and handy luminaires has been designed to illuminate larger areas.

### **TECHNICAL PARAMETERS**

Index: 406485
Light source: LED module

Ingress protection: IP54
Impact resistance: IK10
Rated power of the luminaire [W]\*: 50
Colour temperature [K]: 4000
Luminous flux [Im]\*: 5500
Supply voltage [V]: 220-240



# **MAGNUM STANDARD 50W I CL.WITH SOCKET SCHUKO**

**DETAILED CARD** 

#### **TECHNICAL PARAMETERS TABLE**

Index:	406485
	100.100
ETIM class:	EC000346
Light source:	LED module
Rated power of the luminaire [W]:	50
Colour temperature [K]:	4000
Luminous flux [lm]:	5500
Luminous efficacy [lm/W]:	129
Supply voltage [V]:	220-240
Electrical protection class:	1
Energy efficiency class:	Е
Beam angle [°]:	120
Diffuser material:	PC
Diffuser type:	frozen
Material of the body:	PP
Colour of the body:	green
Dimensions (H/W/T/S) [mm]:	300/480/75
Impact resistance:	IK10

Ingress protection:	IP54
Plug type:	UNI-SCHUKO
Socket type:	SCHUKO
Sockets:	1
Cable length [m]:	3
Net weight [kg]:	3
Category type:	workplace floodlights
LED lifespan L70B50 [h]:	42000
LED lifespan L80B20 [h]:	85000
LED lifespan L90B10 [h]:	140000
Working temperature [°C]:	from -20 to +35
Wire type:	H07RN-F 3×1,5mm
Number on the palette [pcs]:	132
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Warranty [years]:	2
CE certificate:	<u>47/2025</u>
Manual:	Download PDF

Card creation date: 06 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

