MAGNUM HOBBY 50W II KL. OCHR. UNI-SCHUKO

DETAILED CARD





TECHNICAL PARAMETERS

Index:	406492
Ingress protection:	IP54
Impact resistance:	IK10
Rated power of the luminaire [W]*:	50
Colour temperature [K]:	4000
Luminous flux [lm]*:	5500
Supply voltage [V]:	220-240
Electrical protection class:	II
Material of the body:	PP
Colour of the body:	green

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polypropylene (PP). Anti-glare diffuser made of polycarbonate (PC) transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

APPLICATION

The family of durable and handy luminaires has been designed to illuminate larger areas.



MAGNUM HOBBY 50W II KL. OCHR. UNI-SCHUKO

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module
Rated power of the luminaire [W]:	50
Colour temperature [K]:	4000
Luminous flux [Im]:	5500
Supply voltage [V]:	220-240
Electrical protection class:	II
Beam angle [°]:	120
Diffuser material:	PC
Diffuser type:	frozen
Material of the body:	PP
Colour of the body:	green
Dimensions (H/W/T/S) [mm]:	300/480/75
Impact resistance:	IK10
Ingress protection:	IP54

Plug type:	UNI-SCHUKO
Cable length [m]:	3
Net weight [kg]:	3
Warranty [years]:	2
Index:	406492
Category type:	workplace floodlights
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
LED lifespan L70B50 [h]:	42000
LED lifespan L80B20 [h]:	85000
LED lifespan L90B10 [h]:	140000
Working temperature [°C]:	from -20 to +35
Wire type:	H07RN-F 2×1,0mm
Manual:	Download PDF

Card creation date: 17 September 2020



