

# MAGNUM STANDARD 50W II CL.UNI-SCHUKO

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	406492
Light source:	LED module
Ingress protection:	IP54
Impact resistance:	IK10
Rated power of the luminaire [W]*:	50
Colour temperature [K]:	4000
Luminous flux [lm]*:	5500
Supply voltage [V]:	220-240
Electrical protection class:	II
Material of the body:	PP

## CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polypropylene (PP). Anti-glare diffuser made of polycarbonate (PC) transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

## APPLICATION

The family of durable and handy luminaires has been designed to illuminate larger areas.

# MAGNUM STANDARD 50W II CL.UNI-SCHUKO

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	406492	Impact resistance:	IK10
ETIM class:	EC000346	Ingress protection:	IP54
Light source:	LED module	Plug type:	UNI-SCHUKO
Rated power of the luminaire [W]:	50	Cable length [m]:	3
Colour temperature [K]:	4000	Net weight [kg]:	3
Luminous flux [lm]:	5500	Category type:	workplace floodlights
Luminous efficacy [lm/W]:	129	LED lifespan L70B50 [h]:	42000
Supply voltage [V]:	220-240	LED lifespan L80B20 [h]:	85000
Electrical protection class:	II	LED lifespan L90B10 [h]:	140000
Energy efficiency class:	E	Working temperature [°C]:	from -20 to +35
Beam angle [°]:	120	Wire type:	H07RN-F 2×1,0mm
Diffuser material:	PC	Number on the palette [pcs]:	132
Diffuser type:	frozen	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	PP	Warranty [years]:	2
Colour of the body:	green	CE certificate:	<a href="#">47/2025</a>
Dimensions (H/W/T/S) [mm]:	300/480/75	Manual:	<a href="#">Download PDF</a>