

MAGNUM STANDARD 78W I CL.DK

DETAILED CARD



TECHNICAL PARAMETERS

Light source:	LED module
Ingress protection:	IP44
Impact resistance:	IK10
Rated power of the luminaire [W]*:	78
Colour temperature [K]:	4000
Luminous flux [lm]*:	9500
Supply voltage [V]:	220-240
Electrical protection class:	I
Material of the body:	PP
Colour of the body:	green

CHARACTERISTICS

Kompakter und leichter LED-Flutlichtstrahler für professionelle Anwendungen. Gewährleistet gleichmäßige und stabile Richtungsbeleuchtung. Hergestellt aus schlagfestem Polypropylen (PP). Der Anti-Reflex-Diffusor aus Polycarbonat (PC) lässt trotz der matten Oberfläche bis zu 80 % des von den LEDs emittierten Lichts durch. Die kleinere Größe und das kompakte Design machen den Transport bequem. Er besitzt einen beweglichen Arm mit mehreren Einstellungen, der gleichzeitig einen Haken darstellt.

APPLICATION

The family of durable and handy luminaires has been designed to illuminate larger areas.

MAGNUM STANDARD 78W I CL.DK

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	406508	Ingress protection:	IP44
ETIM class:	EC000346	Plug type:	DK
Light source:	LED module	Cable length [m]:	3
Rated power of the luminaire [W]:	78	Net weight [kg]:	3
Colour temperature [K]:	4000	Category type:	workplace floodlights
Luminous flux [lm]:	9500	LED lifespan L70B50 [h]:	42000
Luminous efficacy [lm/W]:	143	LED lifespan L80B10 [h]:	85000
Supply voltage [V]:	220-240	LED lifespan L90B10 [h]:	140000
Electrical protection class:	I	Working temperature [°C]:	from -20 to +35
Beam angle [°]:	120	Wire type:	H07RN-F 2×1,0mm
Diffuser material:	PC	Number on the palette [pcs]:	132
Diffuser type:	frozen	Energy efficiency class:	D
Material of the body:	PP	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Colour of the body:	green	Warranty [years]:	2
Dimensions (H/W/T/S) [mm]:	300/480/75	CE certificate:	47/2025
Impact resistance:	IK10	Manual:	Download PDF

Card creation date: 06 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 47/2025