MAGNUM STANDARD 78W I CL.DK

DETAILED CARD



TECHNICAL PARAMETERS

Light source:	LED module
Ingress protection:	IP44
Impact resistance:	IK10
Rated power of the luminaire [W]*:	78
Colour temperature [K]:	4000
Luminous flux [lm]*:	9500
Supply voltage [V]:	220-240
Electrical protection class:	I
Material of the body:	PP
Colour of the body:	green

CHARACTERISTICS

Kompakter und leichter LED-Flutlichtstrahler für professionelle Anwendungen. Gewährleistet gleichmäßige und stabile Richtungsbeleuchtung. Hergestellt aus schlagfestem Polypropylen (PP). Der Anti-Reflex-Diffusor aus Polycarbonat (PC) lässt trotz der matten Oberfläche bis zu 80 % des von den LEDs emittierten Lichts durch. Die kleinere Größe und das kompakte Design machen den Transport bequem. Er besitzt einen beweglichen Arm mit mehreren Einstellungen, der gleichzeitig einen Haken darstellt.

APPLICATION

The family of durable and handy luminaires has been designed to illuminate larger areas.

MAGNUM STANDARD 78W I CL.DK

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	406508
ETIM class:	EC000346
Light source:	LED module
Rated power of the luminaire [W]:	78
Colour temperature [K]:	4000
Luminous flux [lm]:	9500
Luminous efficacy [lm/W]:	143
Supply voltage [V]:	220-240
Electrical protection class:	I
Beam angle [°]:	120
Diffuser material:	PC
Diffuser type:	frozen
Material of the body:	PP
Colour of the body:	green
Dimensions (H/W/T/S) [mm]:	300/480/75
Impact resistance:	IK10

Ingress protection:	IP44
Plug type:	DK
Cable length [m]:	3
Net weight [kg]:	3
Category type:	workplace floodlights
LED lifespan L70B50 [h]:	42000
LED lifespan L80B10 [h]:	85000
LED lifespan L90B10 [h]:	140000
Working temperature [°C]:	from -20 to +35
Wire type:	H07RN-F 2×1,0mm
Number on the palette [pcs]:	132
Energy efficiency class:	D
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Warranty [years]:	2
CE certificate:	47/2025
Manual:	Download PDF

Card creation date: 06 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 47/2025

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl