

MAGNUM STANDARD 78W 1ST CL. WITH SCHUKO OUTLET

DETAILED CARD



TECHNICAL PARAMETERS

Light source:	LED module
Ingress protection:	IP54
Impact resistance:	IK10
Rated power of the luminaire [W]*:	78
Colour temperature [K]:	4000
Luminous flux [lm]*:	9500
Supply voltage [V]:	220-240
Electrical protection class:	I
Material of the body:	PP
Colour of the body:	green

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polypropylene (PP). Anti-glare diffuser made of polycarbonate (PC) transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

APPLICATION

The family of durable and handy luminaires has been designed to illuminate larger areas.

MAGNUM STANDARD 78W 1ST CL. WITH SCHUKO OUTLET

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	406522	Plug type:	UNI-SCHUKO
ETIM class:	EC000346	Socket type:	SCHUKO
Light source:	LED module	Sockets:	1
Rated power of the luminaire [W]:	78	Cable length [m]:	3
Colour temperature [K]:	4000	Net weight [kg]:	3
Luminous flux [lm]:	9500	Category type:	workplace floodlights
Luminous efficacy [lm/W]:	143	LED lifespan L70B50 [h]:	42000
Supply voltage [V]:	220-240	LED lifespan L80B10 [h]:	85000
Electrical protection class:	I	LED lifespan L90B10 [h]:	140000
Beam angle [°]:	120	Working temperature [°C]:	from -20 to +35
Diffuser material:	PC	Wire type:	H07RN-F 3×1,5mm
Diffuser type:	frozen	Number on the palette [pcs]:	132
Material of the body:	PP	Energy efficiency class:	D
Colour of the body:	green	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Dimensions (H/W/T/S) [mm]:	300/480/75	Warranty [years]:	2
Impact resistance:	IK10	CE certificate:	47/2025
Ingress protection:	IP54	Manual:	Download PDF

Card creation date: 06 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 47/2025