

MAGNUM STANDARD 78W 1ST CL. WITH SCHUKO OUTLET

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|------------------------------------|------------|
| Light source: | LED module |
| Ingress protection: | IP54 |
| Impact resistance: | IK10 |
| Rated power of the luminaire [W]*: | 78 |
| Colour temperature [K]: | 4000 |
| Luminous flux [lm]*: | 9500 |
| Supply voltage [V]: | 220-240 |
| Electrical protection class: | I |
| Material of the body: | PP |
| Colour of the body: | green |

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polypropylene (PP). Anti-glare diffuser made of polycarbonate (PC) transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

APPLICATION

The family of durable and handy luminaires has been designed to illuminate larger areas.

MAGNUM STANDARD 78W 1ST CL. WITH SCHUKO OUTLET

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|------------|------------------------------|---|
| Index: | 406522 | Plug type: | UNI-SCHUKO |
| ETIM class: | EC000346 | Socket type: | SCHUKO |
| Light source: | LED module | Sockets: | 1 |
| Rated power of the luminaire [W]: | 78 | Cable length [m]: | 3 |
| Colour temperature [K]: | 4000 | Net weight [kg]: | 3 |
| Luminous flux [lm]: | 9500 | Category type: | workplace floodlights |
| Luminous efficacy [lm/W]: | 143 | LED lifespan L70B50 [h]: | 42000 |
| Supply voltage [V]: | 220-240 | LED lifespan L80B20 [h]: | 85000 |
| Electrical protection class: | I | LED lifespan L90B10 [h]: | 140000 |
| Beam angle [°]: | 120 | Working temperature [°C]: | from -20 to +35 |
| Diffuser material: | PC | Wire type: | H07RN-F 3×1,5mm |
| Diffuser type: | frozen | Number on the palette [pcs]: | 132 |
| Material of the body: | PP | Energy efficiency class: | D |
| Colour of the body: | green | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Dimensions (H/W/T/S) [mm]: | 300/480/75 | Warranty [years]: | 2 |
| Impact resistance: | IK10 | CE certificate: | 47/2025 |
| Ingress protection: | IP54 | Manual: | Download PDF |

Card creation date: 06 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 47/2025



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl