

MAGNUM HOBBY 78W I KL. OCHR. Z GNIAZDEM DK

DETAILED CARD



TECHNICAL PARAMETERS

Index:	406539
Ingress protection:	IP44
Impact resistance:	IK10
Rated power of the luminaire [W]*:	78
Colour temperature [K]:	4000
Luminous flux [lm]*:	9500
Supply voltage [V]:	220-240
Electrical protection class:	I
Material of the body:	PP
Colour of the body:	green

CHARACTERISTICS

Kompakter und leichter LED-Flutlichtstrahler für professionelle Anwendungen. Gewährleistet gleichmäßige und stabile Richtungsbeleuchtung. Hergestellt aus schlagfestem Polypropylen (PP). Der Anti-Reflex-Diffusor aus Polycarbonat (PC) lässt trotz der matten Oberfläche bis zu 80 % des von den LEDs emittierten Lichts durch. Die kleinere Größe und das kompakte Design machen den Transport bequem. Er besitzt einen beweglichen Arm mit mehreren Einstellungen, der gleichzeitig einen Haken darstellt.

APPLICATION

The family of durable and handy luminaires has been designed to illuminate larger areas.

MAGNUM HOBBY 78W I KL. OCHR. Z GNIAZDEM DK

DETAILED CARD


TECHNICAL PARAMETERS TABLE

Light source:	LED module	Ingress protection:	IP44
Rated power of the luminaire [W]:	78	Dimensions (H/W/T/S) [mm]:	300/480/75
Colour temperature [K]:	4000	Impact resistance:	IK10
Luminous flux [lm]:	9500	Net weight [kg]:	3
Diffuser type:	frozen	Index:	406539
Plug type:	DK	Category type:	workplace floodlights
Supply voltage [V]:	220-240	Warranty [years]:	2
Socket type:	DK	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Electrical protection class:	I	Warranty [years]:	2
Sockets:	1	LED lifespan L70B50 [h]:	42000
Beam angle [°]:	120	LED lifespan L80B20 [h]:	85000
Cable length [m]:	3	LED lifespan L90B10 [h]:	140000
Diffuser material:	PC	Working temperature [°C]:	from -20 to +35
Material of the body:	PP	Wire type:	H07RN-F 3×1,5mm
Colour of the body:	green	Manual:	Download PDF

Card creation date: 17 September 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 129/2023