

MAGNUM STANDARD 78W I CL.WITH SOCKET PL-FR

DETAILED CARD



TECHNICAL PARAMETERS

Light source:	LED module
Ingress protection:	IP54
Impact resistance:	IK10
Rated power of the luminaire [W]*:	78
Colour temperature [K]:	4000
Luminous flux [lm]*:	9500
Supply voltage [V]:	220-240
Electrical protection class:	I
Material of the body:	PP
Colour of the body:	green

CHARACTERISTICS

Kompakter und leichter LED-Flutlichtstrahler für professionelle Anwendungen. Gewährleistet gleichmäßige und stabile Richtungsbeleuchtung. Hergestellt aus schlagfestem Polypropylen (PP). Der Anti-Reflex-Diffusor aus Polycarbonat (PC) lässt trotz der matten Oberfläche bis zu 80 % des von den LEDs emittierten Lichts durch. Die kleinere Größe und das kompakte Design machen den Transport bequem. Er besitzt einen beweglichen Arm mit mehreren Einstellungen, der gleichzeitig einen Haken darstellt.

APPLICATION

The family of durable and handy luminaires has been designed to illuminate larger areas.

MAGNUM STANDARD 78W I CL.WITH SOCKET PL-FR

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	406546	Plug type:	UNI-SCHUKO
ETIM class:	EC000346	Socket type:	PL-FR
Light source:	LED module	Sockets:	1
Rated power of the luminaire [W]:	78	Cable length [m]:	3
Colour temperature [K]:	4000	Net weight [kg]:	3
Luminous flux [lm]:	9500	Category type:	workplace floodlights
Luminous efficacy [lm/W]:	143	LED lifespan L70B50 [h]:	42000
Supply voltage [V]:	220-240	LED lifespan L80B10 [h]:	85000
Electrical protection class:	I	LED lifespan L90B10 [h]:	140000
Beam angle [°]:	120	Working temperature [°C]:	from -20 to +35
Diffuser material:	PC	Wire type:	H07RN-F 3×1,5mm
Diffuser type:	frozen	Number on the palette [pcs]:	132
Material of the body:	PP	Energy efficiency class:	D
Colour of the body:	green	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Dimensions (H/W/T/S) [mm]:	300/480/75	Warranty [years]:	2
Impact resistance:	IK10	CE certificate:	47/2025
Ingress protection:	IP54	Manual:	Download PDF

Card creation date: 06 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 47/2025