

# MAGNUM HOBBY 78W I KL. OCHR. Z GNIAZDEM PL-FR

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	406546
<b>Ingress protection:</b>	IP54
<b>Impact resistance:</b>	IK10
<b>Rated power of the luminaire [W]*:</b>	78
<b>Colour temperature [K]:</b>	4000
<b>Luminous flux [lm]*:</b>	9500
<b>Supply voltage [V]:</b>	220-240
<b>Electrical protection class:</b>	I
<b>Material of the body:</b>	PP
<b>Colour of the body:</b>	green

## CHARACTERISTICS

Kompakter und leichter LED-Flutlichtstrahler für professionelle Anwendungen. Gewährleistet gleichmäßige und stabile Richtungsbeleuchtung. Hergestellt aus schlagfestem Polypropylen (PP). Der Anti-Reflex-Diffusor aus Polycarbonat (PC) lässt trotz der matten Oberfläche bis zu 80 % des von den LEDs emittierten Lichts durch. Die kleinere Größe und das kompakte Design machen den Transport bequem. Er besitzt einen beweglichen Arm mit mehreren Einstellungen, der gleichzeitig einen Haken darstellt.

## APPLICATION

The family of durable and handy luminaires has been designed to illuminate larger areas.

# MAGNUM HOBBY 78W I KL. OCHR. Z GNIAZDEM PL-FR

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Light source:</b>	LED module	<b>Ingress protection:</b>	IP54
<b>Rated power of the luminaire [W]:</b>	78	<b>Dimensions (H/W/T/S) [mm]:</b>	300/480/75
<b>Colour temperature [K]:</b>	4000	<b>Impact resistance:</b>	IK10
<b>Luminous flux [lm]:</b>	9500	<b>Net weight [kg]:</b>	3
<b>Diffuser type:</b>	frozen	<b>Index:</b>	406546
<b>Plug type:</b>	UNI-SCHUKO	<b>Category type:</b>	workplace floodlights
<b>Supply voltage [V]:</b>	220-240	<b>Warranty [years]:</b>	2
<b>Socket type:</b>	PL-FR	<b>Photobiological safety:</b>	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
<b>Electrical protection class:</b>	I	<b>Warranty [years]:</b>	2
<b>Sockets:</b>	1	<b>LED lifespan L70B50 [h]:</b>	42000
<b>Beam angle [°]:</b>	120	<b>LED lifespan L80B20 [h]:</b>	85000
<b>Cable length [m]:</b>	3	<b>LED lifespan L90B10 [h]:</b>	140000
<b>Diffuser material:</b>	PC	<b>Working temperature [°C]:</b>	from -20 to +35
<b>Material of the body:</b>	PP	<b>Wire type:</b>	H07RN-F 3×1,5mm
<b>Colour of the body:</b>	green	<b>Manual:</b>	<a href="#">Download PDF</a>

Card creation date: 17 September 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 129/2023