

# MAGNUM STANDARD 78W II CL.UNI-SCHUKO

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Light source:</b>	LED module
<b>Ingress protection:</b>	IP54
<b>Impact resistance:</b>	IK10
<b>Rated power of the luminaire [W]*:</b>	78
<b>Colour temperature [K]:</b>	4000
<b>Luminous flux [lm]*:</b>	9500
<b>Supply voltage [V]:</b>	220-240
<b>Electrical protection class:</b>	II
<b>Material of the body:</b>	PP
<b>Colour of the body:</b>	green

## CHARACTERISTICS

Kompakter und leichter LED-Flutlichtstrahler für professionelle Anwendungen. Gewährleistet gleichmäßige und stabile Richtungsbeleuchtung. Hergestellt aus schlagfestem Polypropylen (PP). Der Anti-Reflex-Diffusor aus Polycarbonat (PC) lässt trotz der matten Oberfläche bis zu 80 % des von den LEDs emittierten Lichts durch. Die kleinere Größe und das kompakte Design machen den Transport bequem. Er besitzt einen beweglichen Arm mit mehreren Einstellungen, der gleichzeitig einen Haken darstellt.

## APPLICATION

The family of durable and handy luminaires has been designed to illuminate larger areas.

# MAGNUM STANDARD 78W II CL.UNI-SCHUKO

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	406515	<b>Ingress protection:</b>	IP54
<b>ETIM class:</b>	EC000346	<b>Plug type:</b>	UNI-SCHUKO
<b>Light source:</b>	LED module	<b>Cable length [m]:</b>	3
<b>Rated power of the luminaire [W]:</b>	78	<b>Net weight [kg]:</b>	3
<b>Colour temperature [K]:</b>	4000	<b>Category type:</b>	workplace floodlights
<b>Luminous flux [lm]:</b>	9500	<b>LED lifespan L70B50 [h]:</b>	42000
<b>Luminous efficacy [lm/W]:</b>	143	<b>LED lifespan L80B10 [h]:</b>	85000
<b>Supply voltage [V]:</b>	220-240	<b>LED lifespan L90B10 [h]:</b>	140000
<b>Electrical protection class:</b>	II	<b>Working temperature [°C]:</b>	from -20 to +35
<b>Beam angle [°]:</b>	120	<b>Wire type:</b>	H07RN-F 2×1,0mm
<b>Diffuser material:</b>	PC	<b>Number on the palette [pcs]:</b>	132
<b>Diffuser type:</b>	frozen	<b>Energy efficiency class:</b>	D
<b>Material of the body:</b>	PP	<b>Photobiological safety:</b>	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
<b>Colour of the body:</b>	green	<b>Warranty [years]:</b>	2
<b>Dimensions (H/W/T/S) [mm]:</b>	300/480/75	<b>CE certificate:</b>	<a href="#">47/2025</a>
<b>Impact resistance:</b>	IK10	<b>Manual:</b>	<a href="#">Download PDF</a>

Card creation date: 06 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 47/2025