

# MAGNUM STANDARD 32W I CL.DK

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	406430
Light source:	LED module
Ingress protection:	IP44
Impact resistance:	IK10
Rated power of the luminaire [W]*:	32
Colour temperature [K]:	4000
Luminous flux [lm]*:	3600
Supply voltage [V]:	220-240
Electrical protection class:	I
Material of the body:	PP

## CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polypropylene (PP). Anti-glare diffuser made of polycarbonate (PC) transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

## APPLICATION

The luminaire will provide precise illumination of the workplace.

# MAGNUM STANDARD 32W I CL.DK

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	406430	Impact resistance:	IK10
ETIM class:	EC000346	Ingress protection:	IP44
Light source:	LED module	Plug type:	DK
Rated power of the luminaire [W]:	32	Wire type:	H07RN-F 2×1,0mm
Colour temperature [K]:	4000	Cable length [m]:	3
Luminous flux [lm]:	3600	Net weight [kg]:	2
Luminous efficacy [lm/W]:	132	Category type:	workplace floodlights
Supply voltage [V]:	220-240	LED lifespan L70B50 [h]:	42000
Electrical protection class:	I	LED lifespan L80B20 [h]:	85000
Energy efficiency class:	E	LED lifespan L90B10 [h]:	140000
Beam angle [°]:	120	Working temperature [°C]:	from -20 to +35
Diffuser material:	PC	Number on the palette [pcs]:	102
Diffuser type:	frozen	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	PP	Warranty [years]:	2
Colour of the body:	green	CE certificate:	<a href="#">47/2025</a>
Dimensions (H/W/T/S) [mm]:	300/400/100	Manual:	<a href="#">Download PDF</a>

Card creation date: 06 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 47/2025



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)