
# **MAGNUM STANDARD 32W I CL.DK**

**DETAILED CARD** 





## **TECHNICAL PARAMETERS**

Index: 406430

Light source: LED module

Ingress protection: IP44

Impact resistance: IK10

Rated power of the luminaire [W]\*: 32

Colour temperature [K]: 4000

Luminous flux [lm]\*: 3600

Supply voltage [V]: 220-240

Electrical protection class:

Material of the body: PP

#### **CHARACTERISTICS**

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polypropylene (PP). Anti-glare diffuser made of polycarbonate (PC) transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

### APPLICATION

The luminaire will provide precise illumination of the workplace.



# **MAGNUM STANDARD 32W I CL.DK**

**DETAILED CARD** 

#### **TECHNICAL PARAMETERS TABLE**

	1
Index:	406430
Rated power of the luminaire [W]:	32
ETIM class:	EC000346
Colour temperature [K]:	4000
Light source:	LED module
Luminous flux [Im]:	3600
Diffuser type:	frozen
Plug type:	DK
Luminous efficacy [lm/W]:	132
Wire type:	H07RN-F 2×1,0mm
Supply voltage [V]:	220-240
Cable length [m]:	3
Electrical protection class:	1
Energy efficiency class:	E
Beam angle [°]:	120

Ingress protection:	IP44
Diffuser material:	PC
Material of the body:	PP
Colour of the body:	green
Dimensions (H/W/T/S) [mm]:	300/400/100
Impact resistance:	IK10
Net weight [kg]:	2
Category type:	workplace floodlights
LED lifespan L70B50 [h]:	42000
LED lifespan L80B20 [h]:	85000
LED lifespan L90B10 [h]:	140000
Working temperature [°C]:	from -20 to +35
Number on the palette [pcs]:	102
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Warranty [years]:	2
CE certificate:	<u>47/2025</u>
Manual:	Download PDF

Card creation date: 06 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

