MAGNUM HOBBY 32W I KL. OCHR. Z GNIAZDEM DK

DETAILED CARD





Index: 406409
Ingress protection: IP44
Impact resistance: IK10
Rated power of the luminaire [W]*: 32
Colour temperature [K]: 4000
Luminous flux [Im]*: 3600
Supply voltage [V]: 220-240
Electrical protection class: I

PΡ

green

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polypropylene (PP). Anti-glare diffuser made of polycarbonate (PC) transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

APPLICATION

The luminaire will provide precise illumination of the workplace.



Material of the body:

Colour of the body:

MAGNUM HOBBY 32W I KL. OCHR. Z GNIAZDEM DK

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Links annual	LED module
Light source:	LED module
Rated power of the luminaire [W]:	32
Colour temperature [K]:	4000
Luminous flux [lm]:	3600
Supply voltage [V]:	220-240
Electrical protection class:	1
Beam angle [°]:	120
Diffuser material:	PC
Diffuser type:	frozen
Material of the body:	PP
Colour of the body:	green
Dimensions (H/W/T/S) [mm]:	300/400/100
Impact resistance:	IK10
Ingress protection:	IP44
Plug type:	DK

	1
Socket type:	DK
Sockets:	1
Wire type:	H07RN-F 3×1,5mm
Cable length [m]:	3
Net weight [kg]:	2
Index:	406409
Category type:	workplace floodlights
Warranty [years]:	2
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Warranty [years]:	2
LED lifespan L70B50 [h]:	42000
LED lifespan L80B20 [h]:	85000
LED lifespan L90B10 [h]:	140000
Working temperature [°C]:	from -20 to +35
Manual:	Download PDF

Card creation date: 17 September 2020



