

MAGNUM STANDARD 32W I CL.WITH SOCKET PL-FR

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|------------|
| Index: | 406416 |
| Light source: | LED module |
| Ingress protection: | IP54 |
| Impact resistance: | IK10 |
| Rated power of the luminaire [W]*: | 32 |
| Colour temperature [K]: | 4000 |
| Luminous flux [lm]*: | 3600 |
| Supply voltage [V]: | 220-240 |
| Electrical protection class: | I |
| Material of the body: | PP |

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polypropylene (PP). Anti-glare diffuser made of polycarbonate (PC) transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

APPLICATION

The luminaire will provide precise illumination of the workplace.

MAGNUM STANDARD 32W I CL.WITH SOCKET PL-FR

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|--|-------------|-------------------------------------|---|
| Index: | 406416 | Ingress protection: | IP54 |
| ETIM class: | EC000346 | Plug type: | UNI-SCHUKO |
| Light source: | LED module | Socket type: | PL-FR |
| Rated power of the luminaire [W]: | 32 | Sockets: | 1 |
| Colour temperature [K]: | 4000 | Wire type: | H07RN-F 3×1,5mm |
| Luminous flux [lm]: | 3600 | Cable length [m]: | 3 |
| Luminous efficacy [lm/W]: | 132 | Net weight [kg]: | 2 |
| Supply voltage [V]: | 220-240 | Category type: | workplace floodlights |
| Electrical protection class: | I | LED lifespan L70B50 [h]: | 42000 |
| Energy efficiency class: | E | LED lifespan L80B10 [h]: | 85000 |
| Beam angle [°]: | 120 | LED lifespan L90B10 [h]: | 140000 |
| Diffuser material: | PC | Working temperature [°C]: | from -20 to +35 |
| Diffuser type: | frozen | Number on the palette [pcs]: | 102 |
| Material of the body: | PP | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Colour of the body: | green | Warranty [years]: | 2 |
| Dimensions (H/W/T/S) [mm]: | 300/400/100 | CE certificate: | 47/2025 |
| Impact resistance: | IK10 | Manual: | Download PDF |

Card creation date: 06 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 47/2025