

MAGNUM STANDARD 32W I CL.WITH SOCKET PL-FR

DETAILED CARD



TECHNICAL PARAMETERS

Index:	406416
Light source:	LED module
Ingress protection:	IP54
Impact resistance:	IK10
Rated power of the luminaire [W]*:	32
Colour temperature [K]:	4000
Luminous flux [lm]*:	3600
Supply voltage [V]:	220-240
Electrical protection class:	I
Material of the body:	PP

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polypropylene (PP). Anti-glare diffuser made of polycarbonate (PC) transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

APPLICATION

The luminaire will provide precise illumination of the workplace.

MAGNUM STANDARD 32W I CL.WITH SOCKET PL-FR

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	406416	Ingress protection:	IP54
ETIM class:	EC000346	Plug type:	UNI-SCHUKO
Light source:	LED module	Socket type:	PL-FR
Rated power of the luminaire [W]:	32	Sockets:	1
Colour temperature [K]:	4000	Wire type:	H07RN-F 3×1,5mm
Luminous flux [lm]:	3600	Cable length [m]:	3
Luminous efficacy [lm/W]:	132	Net weight [kg]:	2
Supply voltage [V]:	220-240	Category type:	workplace floodlights
Electrical protection class:	I	LED lifespan L70B50 [h]:	42000
Energy efficiency class:	E	LED lifespan L80B20 [h]:	85000
Beam angle [°]:	120	LED lifespan L90B10 [h]:	140000
Diffuser material:	PC	Working temperature [°C]:	from -20 to +35
Diffuser type:	frozen	Number on the palette [pcs]:	102
Material of the body:	PP	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Colour of the body:	green	Warranty [years]:	2
Dimensions (H/W/T/S) [mm]:	300/400/100	CE certificate:	47/2025
Impact resistance:	IK10	Manual:	Download PDF

Card creation date: 06 May 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 47/2025



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl