

MAGNUM HOBBY 32W I KL. OCHR. Z GNIAZDEM SCHUKO

DETAILED CARD



TECHNICAL PARAMETERS

Index:	x
Ingress protection:	IP44; IP54
Impact resistance:	IK10
Rated power of the luminaire [W]*:	32
Colour temperature [K]:	4000
Luminous flux [lm]*:	3600
Supply voltage [V]:	220-240
Electrical protection class:	I; II
Material of the body:	PP
Colour of the body:	zielony

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polypropylene (PP). Anti-glare diffuser made of polycarbonate (PC) transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

APPLICATION

The luminaire will provide precise illumination of the workplace.

MAGNUM HOBBY 32W I KL. OCHR. Z GNIAZDEM SCHUKO

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	moduł LED	Socket type:	DK; PL-FR; SCHUKO
Rated power of the luminaire [W]:	32	Sockets:	1
Colour temperature [K]:	4000	Wire type:	H07RN-F 2×1,0mm; H07RN-F 3×1,5mm
Luminous flux [lm]:	3600	Cable length [m]:	3
Supply voltage [V]:	220-240	Net weight [kg]:	2
Electrical protection class:	I; II	Index:	x
Beam angle [°]:	120	Category type:	workplace floodlights
Diffuser material:	PC	Warranty [years]:	2
Diffuser type:	mrożony	Photobiological safety:	grupa ryzyka 1 (niskie ryzyko)
Material of the body:	PP	Warranty [years]:	2
Colour of the body:	zielony	LED lifespan L70B50 [h]:	42000
Dimensions (H/W/T/S) [mm]:	300/400/100	LED lifespan L80B20 [h]:	85000
Impact resistance:	IK10	LED lifespan L90B10 [h]:	140000
Ingress protection:	IP44; IP54	Working temperature [°C]:	od -20 do +35
Plug type:	DK; UNI-SCHUKO	Manual:	Download PDF