MAGNUM HOBBY 32W II KL. OCHR. UNI-SCHUKO

DETAILED CARD





Index: 406447

Ingress protection: IP54

Impact resistance: IK10

Rated power of the luminaire [W]*: 32

Colour temperature [K]: 4000

Luminous flux [Im]*: 3600

Supply voltage [V]: 220-240

Electrical protection class: II

PΡ

green

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polypropylene (PP). Anti-glare diffuser made of polycarbonate (PC) transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

APPLICATION

The luminaire will provide precise illumination of the workplace.



Material of the body:

Colour of the body:

MAGNUM HOBBY 32W II KL. OCHR. UNI-SCHUKO

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| Nominal power [W]: | 32 |
|-----------------------------------|-----------------|
| Light source: | LED module |
| Colour temperature [K]: | 4000 |
| Rated power of the luminaire [W]: | 32 |
| Luminous flux [Im]: | 3600 |
| Diffuser type: | frozen |
| Plug type: | UNI-SCHUKO |
| Supply voltage [V]: | 220-240 |
| Electrical protection class: | II |
| Beam angle [°]: | 120 |
| Wire type: | H07RN-F 2×1,0mm |
| Diffuser material: | PC |
| Cable length [m]: | 3 |
| Material of the body: | PP |

| Colour of the body: | green |
|---|---|
| Dimensions (H/W/T/S) [mm]: | 300/400/100 |
| Ingress protection: | IP54 |
| Impact resistance: | IK10 |
| Net weight [kg]: | 2 |
| Index: | 406447 |
| Category type: | workplace floodlights |
| Warranty [years]: | 2 |
| | |
| Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Photobiological safety: Warranty [years]: | hazard under normal behavioral |
| | hazard under normal behavioral limitation) |
| Warranty [years]: | hazard under normal behavioral limitation) |
| Warranty [years]: LED lifespan L70B50 [h]: | hazard under normal behavioral limitation) 2 42000 |
| Warranty [years]: LED lifespan L70B50 [h]: LED lifespan L80B20 [h]: | hazard under normal behavioral limitation) 2 42000 85000 |

Card creation date: 17 September 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

