


SQ 300 LED PLUS 2400 LM 830 IP54 II KL. DALI RCR OPAL RAL9005 (25W) 300MM CORRIDOR

DETAILED CARD



TECHNICAL PARAMETERS

Index:	665950
Ingress protection:	IP54
Impact resistance:	IK08
Nominal power [W]:	25
Luminous flux [lm]*:	2400
Colour temperature [K]:	3000
Energy efficiency class:	F
Material of the body:	ABS
Diffuser material:	PS
Diffuser type:	OPAL

CHARACTERISTICS

SQ 300 LED is a new line of square ceiling lamps. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, thanks to which it is characterized by low weight and high impact resistance (IK08). The diffuser made of PC polycarbonate provides the lamp with excellent lighting properties. Integrated LED module provides low power consumption and all the advantages of modern lamps with an LED source. The PLUS version of the luminaire line is equipped with brand components from recognized global manufacturers. It is characterized by extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

APPLICATION

The surface-mounted lamp for ceiling or wall mounting is intended for both indoor use - in rooms with high humidity, passageways, staircases, and outdoor use as façade lighting.


SQ 300 LED PLUS 2400 LM 830 IP54 II KL. DALI RCR OPAL RAL9005 (25W) 300MM CORRIDOR

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	665950	Dimensions of single box [mm]:	305/305/60
Nominal power [W]:	25	Net weight [kg]:	1.098
Rated power of the luminaire [W]:	28	Warranty [years]:	5
Supply voltage [V]:	220 - 240	Category type:	bulkheads
Frequency [Hz]:	50 - 60	Category of application:	educational institutions, HoReCa, commercial facilities
Luminous flux [lm]:	2400	AC voltage range [V]:	176 - 280
Luminous efficacy [lm/W]:	84	LED lifespan L70B50 [h]:	120000
Energy efficiency class:	F	LED lifespan L80B20 [h]:	80000
Electrical protection class:	II	LED lifespan L90B10 [h]:	40000
Colour temperature [K]:	3000	Light distribution type:	open space
Beam angle [°]:	120	SDCM:	≤ 3
Diffuser material:	PS	Power factor:	0.92
Diffuser type:	OPAL	Surge protection [kV]:	1
Diffuser colour:	white	Working temperature [°C]:	from -20 to +35
Optics material:	PMMA	Corridor function:	yes
Material of the body:	ABS	Permeability factor of the diffuser:	0.70
Colour of the body:	black	Glow wire test [°C]:	650
Dimensions (H/W/T/S) [mm]:	300/300/58	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Mounting dimensions [mm]:	210	Warranty [years]:	5
Impact resistance:	IK08	ENEC Certificate:	0316/ENEC/23
Ingress protection:	IP54	CE certificate:	111/2023
Mounting version:	surface	PZH certificate:	B-BK-60212-0479/21
Motion sensor:	yes	Manual:	Download PDF
DIMM DALI:	yes	Plik LDT:	Download

LIGHT CURVES



Card creation date: 03 January 2025
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 111/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl