

# RQ 160 LED N 1700LM MAT 830 (17W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	570483
<b>Ingress protection:</b>	IP33
<b>Nominal power [W]:</b>	17
<b>Luminous flux [lm]*:</b>	1700
<b>Colour temperature [K]:</b>	3000
<b>Colour rendering index:</b>	>80
<b>Energy efficiency class:</b>	E
<b>Material of the body:</b>	ABS
<b>Colour of the body:</b>	white
<b>Diffuser material:</b>	PC

## CHARACTERISTICS

RQ 160 LED N is a new line of round luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

## APPLICATION

Surface-mounted luminaire is especially recommended for offices, spacious corridors and public spaces.

# RQ 160 LED N 1700LM MAT 830 (17W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Nominal power [W]:	17	Material of the body:	ABS
Index:	570483	Colour of the body:	white
Colour temperature [K]:	3000	Mounting dimensions [mm]:	117
Luminous flux [lm]:	1700	Impact resistance:	IK08
Light source:	LED module	Mounting version:	surface
Diffuser type:	MAT	Working temperature [°C]:	from -20 to +35
Ingress protection:	IP33	Number on the palette [pcs]:	364
Rated power of the luminaire [W]:	18	Net weight [kg]:	0.400
Dimensions (H/W/T/S) [mm]:	166/86	LED lifespan L70B50 [h]:	132000
Supply voltage [V]:	220 - 240	LED lifespan L80B20 [h]:	84000
Frequency [Hz]:	50 - 60	LED lifespan L90B10 [h]:	42000
Luminous efficacy [lm/W]:	90	Light distribution type:	lambertian
Energy efficiency class:	E	Photobiological safety:	RG0 - exempt (no photobiological hazard) HoReCa, commercial facilities, educational institutions, art and culture
Electrical protection class:	I	Category of application:	
Colour rendering index:	>80	Warranty [years]:	5
SDCM:	≤ 3	CE certificate:	<a href="#">317/2023</a>
Power factor:	0.99	PZH certificate:	<a href="#">B-BK-60112-0365-2022</a>
Beam angle [°]:	110	Manual:	<a href="#">Download PDF</a>
Diffuser material:	PC	Plik LDT:	<a href="#">Pobierz</a>

# RQ 160 LED N 1700LM MAT 830 (17W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
573637	Suspension RQ160 fi100 white ON/OFF. DALI

Card creation date: 10 December 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 317/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl