

# RQ 160 LED N 1800LM MAT 840 (17W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	570339
<b>Ingress protection:</b>	IP33
<b>Nominal power [W]:</b>	17
<b>Luminous flux [lm]*:</b>	1800
<b>Colour temperature [K]:</b>	4000
<b>Color rendering index (Ra) &gt;:</b>	80
<b>Energy efficiency class:</b>	E
<b>Material of the body:</b>	ABS
<b>Colour of the body:</b>	white
<b>Diffuser material:</b>	PC

## CHARACTERISTICS

RQ 160 LED N is a new line of round luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

## APPLICATION

Surface-mounted luminaire is especially recommended for offices, spacious corridors and public spaces.

# RQ 160 LED N 1800LM MAT 840 (17W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	570339	Mounting dimensions [mm]:	117
Light source:	LED module	Impact resistance:	IK08
Nominal power [W]:	17	Ingress protection:	IP33
Rated power of the luminaire [W]:	18	Mounting version:	surface
Supply voltage [V]:	220 - 240	Working temperature [°C]:	from -20 to +35
Frequency [Hz]:	50 - 60	Number on the palette [pcs]:	364
Luminous flux [lm]:	1800	Net weight [kg]:	0.400
Luminous efficacy [lm/W]:	95	LED lifespan L70B50 [h]:	150000
Energy efficiency class:	E	LED lifespan L80B10 [h]:	100000
Electrical protection class:	I	LED lifespan L90B10 [h]:	50000
Colour temperature [K]:	4000	Light distribution type:	lambertian
Color rendering index (Ra) >:	80	ETIM class:	EC002892
SDCM:	3	Category of application:	educational institutions, HoReCa, commercial facilities
Power factor:	0.99	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Beam angle [°]:	110	Warranty [years]:	5
Diffuser material:	PC	CE certificate:	<a href="#">317/2023</a>
Diffuser type:	matt	PZH certificate:	<a href="#">B-BK-60112-0365-2022</a>
Material of the body:	ABS	Manual:	<a href="#">Download PDF</a>
Colour of the body:	white	Pliik LDT:	<a href="#">Download</a>
Dimensions (H/W/T/S) [mm]:	166/86		

## LIGHT CURVES



# RQ 160 LED N 1800LM MAT 840 (17W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
573637	Suspension RQ160 fi100 white ON/OFF. DALI

Card creation date: 12 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 317/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl