

RQ 160 LED N 2100LM PRM 830 (17W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	570537
Ingress protection:	IP33
Nominal power [W]:	17
Luminous flux [lm]*:	2100
Colour temperature [K]:	3000
Colour rendering index:	80
Energy efficiency class:	D
Material of the body:	ABS
Colour of the body:	white
Diffuser material:	PC

CHARACTERISTICS

RQ 160 LED N is a new line of round luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

APPLICATION

Surface-mounted luminaire is especially recommended for offices, spacious corridors and public spaces.


RQ 160 LED N 2100LM PRM 830 (17W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	570537	Dimensions (H/W/T/S) [mm]:	166/86
Light source:	LED module	Mounting dimensions [mm]:	117
Nominal power [W]:	17	Impact resistance:	IK08
Rated power of the luminaire [W]:	18	Ingress protection:	IP33
Supply voltage [V]:	220 - 240	Mounting version:	surface
Frequency [Hz]:	50 - 60	Working temperature [°C]:	from -20 to +35
Luminous flux [lm]:	2100	Number on the palette [pcs]:	364
Luminous efficacy [lm/W]:	111	Net weight [kg]:	0.400
Energy efficiency class:	D	LED lifespan L70B50 [h]:	132000
Electrical protection class:	I	LED lifespan L80B20 [h]:	84000
Colour temperature [K]:	3000	LED lifespan L90B10 [h]:	42000
Colour rendering index:	80	Light distribution type:	lambertian
SDCM:	≤ 3	Category of application:	educational institutions, HoReCa, commercial facilities
Power factor:	0.99	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Beam angle [°]:	115	Warranty [years]:	5
Diffuser material:	PC	CE certificate:	317/2023
Diffuser type:	PRM	PZH certificate:	B-BK-60112-0365-2022
Material of the body:	ABS	Manual:	Download PDF
Colour of the body:	white		

LIGHT CURVES



RQ 160 LED N 2100LM PRM 830 (17W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
573637	Suspension RQ160 fi100 white ON/OFF. DALI

Card creation date:12 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric andelectronic waste equipment regulations (WEEE).



Certificate CE - Nr: 317/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl