
BARIS 40 LED N VD 1100LM PLX I KL. IP20 579 MM 840 BLACK 15W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	319266
Rated power of the luminaire [W]*:	15
Luminous flux [lm]*:	1100
Colour temperature [K]:	4000
Ingress protection:	IP20
Energy efficiency class:	F
Material of the body:	aluminium
Colour of the body:	black
Diffuser material:	PS
Diffuser type:	OPAL

CHARACTERISTICS

Suspended or surface-mounted luminaire with a very narrow cross-section. The bodies are available as an anodised aluminium profile in grey or as an aluminium profile painted in white or black (other colours available on request). Optical system in the form of an opal cover. The luminaire is equipped with a unique suspension system that facilitates mounting and adjustment of the suspension length. All suspended BARIS LED VD luminaires have slings with a box included in the set.

APPLICATION

The luminaire is intended for indoor use. Unique design, energy-saving LED modules, and possible integration with external lighting control systems in the DALI standard make this luminaire suitable for use in modern office buildings, with particular emphasis on representative rooms.
Versions marked "VD" are only intended for use in traffic zones and corridors inside buildings included in Table 5.1 of EN12464.

BARIS 40 LED N VD 1100LM PLX I KL. IP20 579 MM 840 BLACK 15W


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	319266
EAN:	5905963319266
Light source:	LED
Rated power of the luminaire [W]:	15
Nominal power [W]:	13
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	1100
Luminous efficacy [lm/W]:	70
Energy efficiency class:	F
Electrical protection class:	I
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Diffuser material:	PS
Diffuser type:	OPAL
Diffuser colour:	white
Material of the body:	aluminium
Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	53/40/579

Mounting dimensions [mm]:	510
Ingress protection:	IP20
Mounting version:	surface
Net weight [kg]:	0.510
Category type:	luminaires and linear systems
AC voltage range [V]:	220 - 240
LED lifespan L70B50 [h]:	113500
LED lifespan L80B10 [h]:	71500
LED lifespan L90B10 [h]:	34500
Working temperature [°C]:	from 0 to +35
Category of application:	office lighting
Impact resistance:	IK03
Warranty [years]:	3
CE certificate:	307/2023
ENEC Certificate:	PL BBJ/003/2022/M1/A1
Manual:	Download PDF
Environmental Product Declaration (EPD):	852/2025
ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Plik LDT:	Download

LIGHT CURVES



Card creation date: 13 October 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 307/2023

LENA LIGHTING
Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl