

COMPACT LED HYGIENIC N 4200LM PRM II IP65 620X620 840 (32W)

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|---|
| Index: | 647796 |
| Rated power of the luminaire [W]*: | 33 |
| Luminous flux [lm]*: | 4200 |
| Colour temperature [K]: | 4000 |
| Ingress protection: | IP65 |
| Impact resistance: | IK07 |
| Colour rendering index: | >80 |
| SDCM: | ≤ 3 |
| Energy efficiency class: | D |
| Material of the body: | ABS with the addition of silver ions (2%) |

CHARACTERISTICS

COMPACT LED HYGIENIC is a modified version of the proven COMPACT LED EVO model. The material composition of the diffuser and the body has been enriched with silver ions (2%). Silver ions effectively block the development of pathogens on the luminaire surface and reduce their amount (>99%) over 24 hours of contact. The effectiveness of reducing pathogens is confirmed by the BIOMASTER Certificate.

APPLICATION

COMPACT LED HYGIENIC is designed for rooms requiring special protection against pathogens, such as hospitals, patient rooms, medical clinics. The luminaire has received a certificate confirming that it is suitable for use in clean rooms with a stated air cleanliness class ISO 3 - 9 according to CLEANROOM ISO 14644-1:2015.

COMPACT LED HYGIENIC N 4200LM PRM II IP65 620X620 840 (32W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|---------------|---------------------------|---|
| Index: | 647796 | Diffuser material: | PC with the addition of silver ions (2%) |
| Rated power of the luminaire [W]: | 33 | Material of the body: | ABS with the addition of silver ions (2%) |
| EAN: | 5905963647796 | Colour of the body: | white |
| Colour temperature [K]: | 4000 | Impact resistance: | IK07 |
| Light source: | LED module | Mounting version: | surface |
| Luminous flux [lm]: | 4200 | Working temperature [°C]: | from -20 to +35 |
| Diffuser type: | PRM | Net weight [kg]: | 4.300 |
| Nominal power [W]: | 32 | Warranty [years]: | 5 |
| Ingress protection: | IP65 | Category type: | louvres |
| Frequency [Hz]: | 50 - 60 | AC voltage range [V]: | 220 - 240 |
| Dimensions (H/W/T/S) [mm]: | 620/620/66 | LED lifespan L70B50 [h]: | 132000 |
| Luminous efficacy [lm/W]: | 127 | LED lifespan L80B20 [h]: | 84000 |
| Energy efficiency class: | D | LED lifespan L90B10 [h]: | 42000 |
| Electrical protection class: | II | CE certificate: | 247/2023 |
| Colour rendering index: | >80 | PZH certificate: | B-BK-60212-0620/20 |
| SDCM: | ≤ 3 | Manual: | Download PDF |
| Power factor: | 0.95 | Plik LDT: | |
| Beam angle [°]: | 120 | | |

COMPACT LED HYGIENIC N 4200LM PRM II IP65 620X620 840 (32W)

DETAILED CARD

ACCESSORIES AVAILABLE

| index | Name |
|--------|---|
| 630033 | Plasterboard mounting brackets (4 pcs) |
| 904349 | Safety suspension (modular ceiling) |
| 630279 | Compact - Uchwyt do mocowania natynkowego - specjalny / Holder for surface mounting - special |
| 999543 | Plasterboard recessing kit 630x630 white (steel version) |



Plasterboard mounting brackets (4 pcs) (630033)



Safety suspension (modular ceiling) (904349)



Compact - Uchwyt do mocowania natynkowego - specjalny / Holder for surface mounting - special (630279)



Plasterboard recessing kit 630x630 white (steel version) (999543)

Card creation date: 03 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 247/2023