

# COMPACT LED HYGIENIC P 5950LM PRM I IP65 595X595 940 (60W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	647758
<b>Rated power of the luminaire [W]*:</b>	65
<b>Luminous flux [lm]*:</b>	5950
<b>Colour temperature [K]:</b>	4000
<b>Ingress protection:</b>	IP65
<b>Impact resistance:</b>	IK07
<b>Colour rendering index:</b>	>90
<b>SDCM:</b>	≤ 3
<b>Energy efficiency class:</b>	F
<b>Material of the body:</b>	ABS with the addition of silver ions (2%)

## CHARACTERISTICS

COMPACT LED HYGIENIC is a modified version of the proven COMPACT LED EVO model. The material composition of the diffuser and the body has been enriched with silver ions (2%). Silver ions effectively block the development of pathogens on the luminaire surface and reduce their amount (>99%) over 24 hours of contact. The effectiveness of reducing pathogens is confirmed by the BIOMASTER Certificate.

## APPLICATION

COMPACT LED HYGIENIC is designed for rooms requiring special protection against pathogens, such as hospitals, patient rooms, medical clinics. The luminaire has received a certificate confirming that it is suitable for use in clean rooms with a stated air cleanliness class ISO 3 - 9 according to CLEANROOM ISO 14644-1:2015.

# COMPACT LED HYGIENIC P 5950LM PRM I IP65 595X595 940 (60W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	647758	<b>Diffuser material:</b>	PC with the addition of silver ions (2%)
<b>Rated power of the luminaire [W]:</b>	65	<b>Material of the body:</b>	ABS with the addition of silver ions (2%)
<b>EAN:</b>	5905963647758	<b>Colour of the body:</b>	white
<b>Colour temperature [K]:</b>	4000	<b>Impact resistance:</b>	IK07
<b>Light source:</b>	LED module	<b>Mounting version:</b>	recessed
<b>Luminous flux [lm]:</b>	5950	<b>Working temperature [°C]:</b>	from -20 to +35
<b>Diffuser type:</b>	PRM	<b>Net weight [kg]:</b>	2.200
<b>Nominal power [W]:</b>	60	<b>Warranty [years]:</b>	5
<b>Ingress protection:</b>	IP65	<b>Category type:</b>	louvres
<b>Frequency [Hz]:</b>	50 - 60	<b>AC voltage range [V]:</b>	220 - 240
<b>Dimensions (H/W/T/S) [mm]:</b>	595/595/71	<b>LED lifespan L70B50 [h]:</b>	115000
<b>Luminous efficacy [lm/W]:</b>	92	<b>LED lifespan L80B20 [h]:</b>	72000
<b>Energy efficiency class:</b>	F	<b>LED lifespan L90B10 [h]:</b>	35000
<b>Electrical protection class:</b>	I	<b>CE certificate:</b>	<a href="#">190/2023</a>
<b>Colour rendering index:</b>	>90	<b>PZH certificate:</b>	<a href="#">B-BK-60212-0620/20</a>
<b>SDCM:</b>	≤ 3	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Power factor:</b>	0.98	<b>Plik LDT:</b>	
<b>Beam angle [°]:</b>	120		

# COMPACT LED HYGIENIC P 5950LM PRM I IP65 595X595 940 (60W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
630033	Plasterboard mounting brackets (4 pcs)
904349	Safety suspension (modular ceiling)
630279	Compact - Uchwyt do mocowania natynkowego - specjalny / Holder for surface mounting - special
999543	Plasterboard recessing kit 630x630 white (steel version)



Plasterboard mounting brackets (4 pcs) (630033)



Safety suspension (modular ceiling) (904349)



Compact - Uchwyt do mocowania natynkowego - specjalny / Holder for surface mounting - special (630279)



Plasterboard recessing kit 630x630 white (steel version) (999543)

Card creation date: 03 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 190/2023