

BARIS 40 LED BRACKET 1400LM PLX I KL. IP44 579 MM 840 WHITE 16W

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|------------------------------------|-----------------------|
| Rated power of the luminaire [W]*: | 16 |
| Luminous flux [lm]*: | 1400 |
| Colour temperature [K]: | 4000 |
| Ingress protection: | IP44 |
| Energy efficiency class: | F |
| Material of the body: | aluminium |
| Colour of the body: | white |
| Diffuser material: | PS |
| Diffuser type: | OPAL |
| Mounting version: | surface, wall mounted |

CHARACTERISTICS

A luminaire with a very narrow cross-section. The bodies are available as an anodised aluminium profile in grey or as an aluminium profile painted in white or black (other colours available on request). Optical system in the form of an opal cover. The optical system in the form of a prismatic diaphragm reduces glare and is characterized by a greater light transmittance than the opal diffuser, which has a direct impact on a higher value of luminous efficacy.

APPLICATION

The unique design predisposes these luminaires to illuminate: offices, conference rooms, and other representative spaces, in offices, passageways, sanitary rooms, and bathrooms (wall lamps), in public utility buildings.

Versions marked "VD" are only intended for use in traffic zones and corridors inside buildings included in Table 5.1 of EN12464.

BARIS 40 LED BRACKET 1400LM PLX I KL. IP44 579 MM 840 WHITE 16W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|---------------|--------------------------------|---------------------------------------|
| Index: | 318962 | Mounting dimensions [mm]: | 165 |
| EAN: | 5905963318962 | Ingress protection: | IP44 |
| Light source: | LED | Mounting version: | surface, wall mounted |
| Rated power of the luminaire [W]: | 16 | Dimensions of single box [mm]: | 76/56/595 |
| Nominal power [W]: | 14 | Number on the palette [pcs]: | 80 |
| Frequency [Hz]: | 50 - 60 | Net weight [kg]: | 0.690 |
| Luminous flux [lm]: | 1400 | Category type: | luminaires and linear systems |
| Luminous efficacy [lm/W]: | 85 | AC voltage range [V]: | 220 - 240 |
| Energy efficiency class: | F | LED lifespan L70B50 [h]: | 108500 |
| Electrical protection class: | I | LED lifespan L80B20 [h]: | 68500 |
| Colour temperature [K]: | 4000 | LED lifespan L90B10 [h]: | 33000 |
| Colour rendering index: | 80 | Impact resistance: | IK06 |
| SDCM: | ≤ 3 | Warranty [years]: | 5 |
| Diffuser material: | PS | CE certificate: | 240/2023 |
| Diffuser type: | OPAL | ENEC Certificate: | PL BBJ/012/2021/M1/A1 |
| Diffuser colour: | white | PZH certificate: | B-BK-60212-0109/21 |
| Material of the body: | aluminium | Manual: | Download PDF |
| Colour of the body: | white | Plik LDT: | Download |
| Dimensions (H/W/T/S) [mm]: | 53/71/579 | | |

LIGHT CURVES

