FLATO LED FL 3800LM 840 IP44 II KL. 0,25M NO CONNECTOR WHITE (41W)

DETAILED CARD





TECHNICAL PARAMETERS

Index:	622182
Rated power of the luminaire [W]*:	45
Colour temperature [K]:	4000
Luminous flux [lm]*:	3800
Ingress protection:	IP44
Impact resistance:	IK07
Color rendering index (Ra) >:	80
Electrical protection class:	II
Energy efficiency class:	F
Material of the body:	PP

CHARACTERISTICS

Compact LED floodlight ensuring even and stable directional lighting. The luminaire body, made of copolymer with rubber, increases its durability. The luminaire is equipped with anti-glare diffuser made of frosted PC with an UV stabiliser, which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. Also equipped with a comfortable mounting arm offering wide angle adjustment.

APPLICATION

Compact floodlight providing even and stable directional lighting. It is used for general lighting: facades of buildings, farm buildings, yards, billboards, advertising boards, above gates and in front of building entrances.



FLATO LED FL 3800LM 840 IP44 II KL. 0,25M NO CONNECTOR WHITE (41W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	622182
Light source:	LED module
Rated power of the luminaire [W]:	45
Nominal power [W]:	41
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Luminous flux [Im]:	3800
Luminous efficacy [lm/W]:	76
Energy efficiency class:	F
Electrical protection class:	II
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
Surge protection [kV]:	1
Diffuser material:	PC
Diffuser type:	OPAL
Material of the body:	PP
Colour of the body:	white
	•

Dimensions (H/W/T/S) [mm]:	285/261/64
Mounting dimensions [mm]:	20
Impact resistance:	IK07
Ingress protection:	IP44
Mounting version:	surface, wall mounted
Working temperature [°C]:	from -40 to +35
Wire type:	H07RN-F 2x1
Cable length [m]:	0.25
Net weight [kg]:	1.060
Warranty [years]:	5
Category type:	floodlights
AC voltage range [V]:	220-240
LED lifespan L70B50 [h]:	120000
LED lifespan L80B20 [h]:	75000
LED lifespan L90B10 [h]:	36000
Manual:	Download PDF
CE certificate:	<u>189/2023</u>

TECHNICAL DETAILS



FLATO FL LED handle

Card creation date: 05 November 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%





Page 2/2