

FLATO LED FL 3800LM 840 IP44 II KL. 0.25M NO CONNECTOR WHITE (41W) PIR

DETAILED CARD



TECHNICAL PARAMETERS

Index:	622205
Rated power of the luminaire [W]*:	46
Colour temperature [K]:	4000
Luminous flux [lm]*:	3800
Ingress protection:	IP44
Impact resistance:	IK07
Colour rendering index:	>80
Electrical protection class:	II
Energy efficiency class:	F
Material of the body:	PP

CHARACTERISTICS

Compact LED floodlight ensuring even and stable directional lighting. The luminaire body, made of copolymer with rubber, increases its durability. The luminaire is equipped with anti-glare diffuser made of frosted PC with an UV stabiliser, which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. Also equipped with a comfortable mounting arm offering wide angle adjustment.

APPLICATION

Compact floodlight providing even and stable directional lighting. It is used for general lighting: facades of buildings, farm buildings, yards, billboards, advertising boards, above gates and in front of building entrances.

FLATO LED FL 3800LM 840 IP44 II KL. 0.25M NO CONNECTOR WHITE (41W) PIR

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	622205	Dimensions (H/W/T/S) [mm]:	285/261/64
Rated power of the luminaire [W]:	46	Mounting dimensions [mm]:	20
Light source:	LED module	Impact resistance:	IK07
Colour temperature [K]:	4000	Ingress protection:	IP44
Luminous flux [lm]:	3800	Mounting version:	surface, wall mounted
Nominal power [W]:	41	Working temperature [°C]:	from -20 to +35
Diffuser type:	OPAL	Wire type:	H07RN-F 2x1
Supply voltage [V]:	220 - 240	Cable length [m]:	0.25
Frequency [Hz]:	50 - 60	Net weight [kg]:	1.060
Luminous efficacy [lm/W]:	76	Warranty [years]:	2
Energy efficiency class:	F	Category type:	floodlights
Electrical protection class:	II	AC voltage range [V]:	220-240
Colour rendering index:	>80	LED lifespan L70B50 [h]:	120000
Surge protection [kV]:	1	LED lifespan L80B20 [h]:	75000
Diffuser material:	PC	LED lifespan L90B10 [h]:	36000
Material of the body:	PP	Manual:	Download PDF
Colour of the body:	white	CE certificate:	189/2023
PIR:	yes		

TECHNICAL DETAILS



FLATO FL LED handle

Card creation date: 05 November 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 189/2023