

SMART LED EVO NT END 1412MM 5700LM PRM I KL OCHR. ANODA CO IP20 840 (50W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	x
Ingress protection:	IP20
Luminous flux [lm]*:	2250 - 5950
Colour temperature [K]:	3000; 4000
Colour rendering index:	>80
DIMM DALI:	yes
Colour of the body:	anoda CO; biały; czarny
Diffuser type:	OPAL; PRM
Version:	end; middle
Mounting version:	natynkowy; zwieszany

CHARACTERISTICS

The system of a surface mounted continuous lighting luminaire with a very narrow cross-section. Its body is made of anodized gray aluminum profile. Optical system designed in two variants: opal or prismatic diffuser. The luminaire is equipped with a unique suspension system that facilitates mounting of the luminaire and adjustment of the suspension length.

APPLICATION

Modular continuous lighting system luminaire for internal use. It can be used as a primary source of light in offices also when eyesight concentration is required. Unique design, energy-efficient LED panels and the possibility of using DALI systems dedicate the luminaire for use in modern office buildings, with particular emphasis on representative rooms.

SMART LED EVO NT END 1412MM 5700LM PRM I KL OCHR. ANODA CO IP20 840 (50W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	moduł LED	Colour of the body:	anoda CO; biały; czarny
Nominal power [W]:	20	Dimensions (H/W/T/S) [mm]:	65/55/1123; 65/55/1131; 65/55/1404; 65/55/1412; 65/55/1420; 75/55/1123; 75/55/1131; 75/55/1404
Supply voltage [V]:	220-240	Ingress protection:	IP20
Frequency [Hz]:	50-60	Mounting version:	natynkowy; zwieszany
Luminous flux [lm]:	2250 - 5950	Working temperature [°C]:	od 0 do +25
Energy efficiency class:	A+; E	DIMM DALI:	yes
Electrical protection class:	I	Net weight [kg]:	1.950; 2.370; 2.470; 2.500
Colour temperature [K]:	3000; 4000	CE certificate:	35/2017
Colour rendering index:	>80	Index:	x
SDCM:	≤ 3	Category type:	systems
Power factor:	0.91; 0.95	Version:	end; middle
Diffuser material:	PMMA	ETIM class:	EC000282
Diffuser type:	OPAL; PRM	Photobiological safety:	grupa ryzyka 1 (niskie ryzyko)
Material of the body:	aluminium	Manual:	Pobierz PDF