

SOLEO END 1131MM 2950LM PLX I KL OCHR. CZARNY MAT IP20 830 (30W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	652950.
Ingress protection:	IP20
Luminous flux [lm]*:	2950
Colour temperature [K]:	3000
Colour rendering index:	>80
Colour of the body:	black
Diffuser type:	OPAL
Version:	end
Mounting version:	suspended

CHARACTERISTICS

The system of a suspended continuous lighting luminaire with a very narrow cross-section. Its body is made of anodized gray aluminum profile. Optical system designed in two variants: opal or prismatic diffuser. The luminaire is equipped with a unique suspension system that facilitates mounting of the luminaire and adjustment of the suspension length.

APPLICATION

Suspended modular continuous lighting system luminaire for internal use. It can be used as a primary source of light in offices also when eyesight concentration is required. Unique design, energy-efficient LED panels and the possibility of using DALI systems dedicate the luminaire for use in modern office buildings, with particular emphasis on representative rooms.

SOLEO END 1131MM 2950LM PLX I KL OCHR. CZARNY MAT IP20 830 (30W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	30	Colour rendering index:	>80
Light source:	LED module	SDCM:	≤ 3
Colour temperature [K]:	3000	Power factor:	0.95
Luminous flux [lm]:	2950	Diffuser material:	PMMA
Rated power of the luminaire [W]:	31.60	Material of the body:	aluminium
Diffuser type:	OPAL	Ingress protection:	IP20
Supply voltage [V]:	220-240	Mounting version:	suspended
Frequency [Hz]:	50 - 60	Working temperature [°C]:	from 0 to +25
Version:	end	Net weight [kg]:	1.950
Colour of the body:	black	CE certificate:	35/2017
Luminous efficacy [lm/W]:	93	Index:	652950.
Dimensions (H/W/T/S) [mm]:	65/55/1131	Category type:	systems
Energy efficiency class:	A+	ETIM class:	EC000282
Electrical protection class:	I	Manual:	Download PDF

Card creation date: 17 September 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 35/2017