



## TECHNICAL PARAMETERS

---

<b>Index:</b>	652691.
<b>Ingress protection:</b>	IP20
<b>Luminous flux [lm]*:</b>	3600
<b>Colour temperature [K]:</b>	4000
<b>Colour rendering index:</b>	>80
<b>Colour of the body:</b>	black
<b>Diffuser type:</b>	PRM
<b>Version:</b>	end
<b>Mounting version:</b>	suspended

## CHARACTERISTICS

---

Aufgehängtes oder oberflächenmontiertes Lichtleitungssystem mit sehr schmalen Querschnitt. Sein Gehäuse wurde aus eloxiertem grauem Aluminiumprofil gefertigt. Optisches System in zwei Varianten: opaler oder prismatischer Diffusor. Die Leuchte ist mit einem einzigartigen Aufhängungssystem ausgestattet, das das Anbringen und Einstellen der Aufhängung erleichtert.

## APPLICATION

---

Beleuchtungssystem für den Inneneinsatz. Es wird als Hauptlichtquelle verwendet und fördert Büroarbeit, die Konzentration des Sehvermögens erfordert. Das einzigartige Design, die energiesparenden LED-Panels und die Möglichkeit der Zusammenarbeit mit externen Lichtsteuersystemen in den DALI-Standardleuchten für den Einsatz in modernen Bürogebäuden mit besonderem Schwerpunkt auf repräsentative Räume.

DETAILED CARD

TECHNICAL PARAMETERS TABLE

<b>Light source:</b>	LED module	<b>Diffuser type:</b>	PRM
<b>Nominal power [W]:</b>	30	<b>Material of the body:</b>	aluminium
<b>Rated power of the luminaire [W]:</b>	31.60	<b>Colour of the body:</b>	black
<b>Supply voltage [V]:</b>	220-240	<b>Dimensions (H/W/T/S) [mm]:</b>	65/55/1131
<b>Frequency [Hz]:</b>	50 - 60	<b>Ingress protection:</b>	IP20
<b>Luminous flux [lm]:</b>	3600	<b>Mounting version:</b>	suspended
<b>Luminous efficacy [lm/W]:</b>	113	<b>Working temperature [°C]:</b>	from 0 to +25
<b>Energy efficiency class:</b>	A+	<b>Net weight [kg]:</b>	1.950
<b>Electrical protection class:</b>	I	<b>CE certificate:</b>	35/2017
<b>Colour temperature [K]:</b>	4000	<b>Index:</b>	652691.
<b>Colour rendering index:</b>	>80	<b>Category type:</b>	systems
<b>SDCM:</b>	≤ 3	<b>Version:</b>	end
<b>Power factor:</b>	0.95	<b>ETIM class:</b>	EC000282
<b>Diffuser material:</b>	PMMA	<b>Manual:</b>	Download PDF

Card creation date: 09 December 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 35/2017