SOLEO END 1131MM 5350LM PLX I KL OCHR. BIAŁY MAT IP20 840 (48W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	652967.
Ingress protection:	IP20
Luminous flux [lm]*:	5350
Colour temperature [K]:	4000
Colour rendering index:	>80
Colour of the body:	white
Diffuser type:	OPAL
Version:	end
Mounting version:	suspended

CHARACTERISTICS

The system of a suspended continuous lighting luminaire with a very narrow cross-section. Its body is made of anodized gray aluminum profile. Optical system designed in two variants: opal or prismatic diffuser. The luminaire is equipped with a unique suspension system that facilitates mounting of the luminaire and adjustment of the suspension length.

APPLICATION

Suspended modular continuous lighting system luminaire for internal use. It can used as a primary source of light in offices also when eyesight concentration is required. Unique design, energy-efficient LED panels and the possibility of using DALI systems dedicate the luminaire for use in modern office buildings, with particular emphasis on representative rooms.

SOLEO END 1131MM 5350LM PLX I KL OCHR. BIAŁY MAT IP20 840 (48W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	**Diffuser type:**	OPAL
Nominal power [W]:	48	**Material of the body:**	aluminium
Rated power of the luminaire [W]:	49.50	**Colour of the body:**	white
Supply voltage [V]:	220-240	**Dimensions (H/W/T/S) [mm]:**	65/55/1131
Frequency [Hz]:	50 - 60	**Ingress protection:**	IP20
Luminous flux [lm]:	5350	**Mounting version:**	suspended
Luminous efficacy [lm/W]:	108	**Working temperature [°C]:**	from 0 to +25
Energy efficiency class:	A+	**Net weight [kg]:**	1.950
Electrical protection class:	I	**CE certificate:**	35/2017
Colour temperature [K]:	4000	**Index:**	652967.
Colour rendering index:	>80	**Category type:**	systems
SDCM:	≤ 3	**Version:**	end
Power factor:	0.95	**ETIM class:**	EC000282
Diffuser material:	PMMA	**Manual:**	Download PDF

Card creation date: 17 September 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 35/2017

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl