

SOLEO END 1412MM 3350LM PRM I KL OCHR. BIAŁY MAT IP20 830 (30W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	651465.
Ingress protection:	IP20
Luminous flux [lm]*:	3350
Colour temperature [K]:	3000
Colour rendering index:	>80
Colour of the body:	white
Diffuser type:	PRM
Version:	end
Mounting version:	suspended

CHARACTERISTICS

The system of a suspended continuous lighting luminaire with a very narrow cross-section. Its body is made of anodized gray aluminum profile. Optical system designed in two variants: opal or prismatic diffuser. The luminaire is equipped with a unique suspension system that facilitates mounting of the luminaire and adjustment of the suspension length.

APPLICATION

Suspended modular continuous lighting system luminaire for internal use. It can used as a primary source of light in offices also when eyesight concentration is required. Unique design, energy-efficient LED panels and the possibility of using DALI systems dedicate the luminaire for use in modern office buildings, with particular emphasis on representative rooms.

SOLEO END 1412MM 3350LM PRM I KL OCHR. BIAŁY MAT IP20 830 (30W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Diffuser type:	PRM
Nominal power [W]:	30	Material of the body:	aluminium
Rated power of the luminaire [W]:	30.80	Colour of the body:	white
Supply voltage [V]:	220-240	Dimensions (H/W/T/S) [mm]:	65/55/1412
Frequency [Hz]:	50 - 60	Ingress protection:	IP20
Luminous flux [lm]:	3350	Mounting version:	suspended
Luminous efficacy [lm/W]:	108	Working temperature [°C]:	from 0 to +25
Energy efficiency class:	A+	Net weight [kg]:	2.370
Electrical protection class:	I	CE certificate:	35/2017
Colour temperature [K]:	3000	Index:	651465.
Colour rendering index:	>80	Category type:	systems
SDCM:	≤ 3	Version:	end
Power factor:	0.91	ETIM class:	EC000282
Diffuser material:	PMMA	Manual:	Download PDF

Card creation date: 17 September 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 35/2017