

SOLEO END 1412MM 5700LM PRM I KL OCHR. BIAŁY MAT IP20 840 (50W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	x
Ingress protection:	IP20
Luminous flux [lm]*:	2250 - 5950
Colour temperature [K]:	3000; 4000
Colour rendering index:	>80
DIMM DALI:	yes
Colour of the body:	anoda CO; biały; czarny
Diffuser type:	OPAL; PRM
Version:	end; middle
Mounting version:	natynkowy; zwieszany

CHARACTERISTICS

The system of a suspended continuous lighting luminaire with a very narrow cross-section. Its body is made of anodized gray aluminum profile. Optical system designed in two variants: opal or prismatic diffuser. The luminaire is equipped with a unique suspension system that facilitates mounting of the luminaire and adjustment of the suspension length.

APPLICATION

Suspended modular continuous lighting system luminaire for internal use. It can be used as a primary source of light in offices also when eyesight concentration is required. Unique design, energy-efficient LED panels and the possibility of using DALI systems dedicate the luminaire for use in modern office buildings, with particular emphasis on representative rooms.

SOLEO END 1412MM 5700LM PRM I KL OCHR. BIAŁY MAT IP20 840 (50W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	moduł LED	Colour of the body:	anoda C0; biały; czarny
Nominal power [W]:	20	Dimensions (H/W/T/S) [mm]:	65/55/1123; 65/55/1131; 65/55/1404; 65/55/1412; 65/55/1420; 75/55/1123; 75/55/1131; 75/55/1404
Supply voltage [V]:	220-240	Ingress protection:	IP20
Frequency [Hz]:	50-60	Mounting version:	natynkowy; zwieszany
Luminous flux [lm]:	2250 - 5950	Working temperature [°C]:	od 0 do +25
Energy efficiency class:	A+; E	DIMM DALI:	yes
Electrical protection class:	I	Net weight [kg]:	1.950; 2.370; 2.470; 2.500
Colour temperature [K]:	3000; 4000	CE certificate:	35/2017
Colour rendering index:	>80	Index:	x
SDCM:	≤ 3	Category type:	systems
Power factor:	0.91; 0.95	Version:	end; middle
Diffuser material:	PMMA	ETIM class:	EC000282
Diffuser type:	OPAL; PRM	Photobiological safety:	grupa ryzyka 1 (niskie ryzyko)
Material of the body:	aluminium	Manual:	Pobierz PDF