

SOLEO NT END 1131MM 4900LM PLX I KL OCHR. BIAŁY MAT IP20 830 (48W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	649783.
Ingress protection:	IP20
Luminous flux [lm]*:	4900
Colour temperature [K]:	3000
Colour rendering index:	>80
Colour of the body:	white
Diffuser type:	OPAL
Version:	end
Mounting version:	surface

CHARACTERISTICS

The system of a surface mounted continuous lighting luminaire with a very narrow cross-section. Its body is made of anodized gray aluminum profile. Optical system designed in two variants: opal or prismatic diffuser. The luminaire is equipped with a unique suspension system that facilitates mounting of the luminaire and adjustment of the suspension length.

APPLICATION

Modular continuous lighting system luminaire for internal use. It can be used as a primary source of light in offices also when eyesight concentration is required. Unique design, energy-efficient LED panels and the possibility of using DALI systems dedicate the luminaire for use in modern office buildings, with particular emphasis on representative rooms.

SOLEO NT END 1131MM 4900LM PLX I KL OCHR. BIAŁY MAT IP20 830 (48W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Diffuser type:	OPAL
Nominal power [W]:	48	Material of the body:	aluminium
Rated power of the luminaire [W]:	49.50	Colour of the body:	white
Supply voltage [V]:	220-240	Dimensions (H/W/T/S) [mm]:	75/55/1131
Frequency [Hz]:	50 - 60	Ingress protection:	IP20
Luminous flux [lm]:	4900	Mounting version:	surface
Luminous efficacy [lm/W]:	98	Working temperature [°C]:	from 0 to +25
Energy efficiency class:	A+	Net weight [kg]:	1.950
Electrical protection class:	I	CE certificate:	35/2017
Colour temperature [K]:	3000	Index:	649783.
Colour rendering index:	>80	Category type:	systems
SDCM:	≤ 3	Version:	end
Power factor:	0.95	ETIM class:	EC000282
Diffuser material:	PMMA	Manual:	Download PDF

Card creation date: 17 September 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 35/2017



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl