



TECHNICAL PARAMETERS

| | |
|--------------------------------|---------|
| Index: | 649158. |
| Ingress protection: | IP20 |
| Luminous flux [lm]*: | 2450 |
| Colour temperature [K]: | 4000 |
| Colour rendering index: | >80 |
| Colour of the body: | black |
| Diffuser type: | PRM |
| Version: | end |
| Mounting version: | surface |

CHARACTERISTICS

The system of a surface mounted continuous lighting luminaire with a very narrow cross-section. Its body is made of anodized gray aluminum profile. Optical system designed in two variants: opal or prismatic diffuser. The luminaire is equipped with a unique suspension system that facilitates mounting of the luminaire and adjustment of the suspension length.

APPLICATION

Modular continuous lighting system luminaire for internal use. It can be used as a primary source of light in offices also when eyesight concentration is required. Unique design, energy-efficient LED panels and the possibility of using DALI systems dedicate the luminaire for use in modern office buildings, with particular emphasis on representative rooms.

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|--|------------|-----------------------------------|---------------|
| Light source: | LED module | Diffuser type: | PRM |
| Nominal power [W]: | 20 | Material of the body: | aluminium |
| Rated power of the luminaire [W]: | 21 | Colour of the body: | black |
| Supply voltage [V]: | 220-240 | Dimensions (H/W/T/S) [mm]: | 65/55/1412 |
| Frequency [Hz]: | 50 - 60 | Ingress protection: | IP20 |
| Luminous flux [lm]: | 2450 | Mounting version: | surface |
| Luminous efficacy [lm/W]: | 116 | Working temperature [°C]: | from 0 to +25 |
| Energy efficiency class: | A+ | Net weight [kg]: | 2.370 |
| Electrical protection class: | I | CE certificate: | 35/2017 |
| Colour temperature [K]: | 4000 | Index: | 649158. |
| Colour rendering index: | >80 | Category type: | systems |
| SDCM: | ≤ 3 | Version: | end |
| Power factor: | 0.95 | ETIM class: | EC000282 |
| Diffuser material: | PMMA | Manual: | Download PDF |

Card creation date: 17 September 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 35/2017



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl