

# SMART LED EVO MIDDLE 1123MM 5350LM PLX I KL OCHR. ANODA CO IP20 840 (48W)

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	652486.
Ingress protection:	IP20
Luminous flux [lm]*:	5350
Colour temperature [K]:	4000
Colour rendering index:	>80
Colour of the body:	C0 anode
Diffuser type:	OPAL
Version:	middle
Mounting version:	suspended

## CHARACTERISTICS

The system of a suspended continuous lighting luminaire with a very narrow cross-section. Its body is made of anodized gray aluminum profile. Optical system designed in two variants: opal or prismatic diffuser. The luminaire is equipped with a unique suspension system that facilitates mounting of the luminaire and adjustment of the suspension length.

## APPLICATION

Suspended modular continuous lighting system luminaire for internal use. It can used as a primary source of light in offices also when eyesight concentration is required. Unique design, energy-efficient LED panels and the possibility of using DALI systems dedicate the luminaire for use in modern office buildings, with particular emphasis on representative rooms.

# SMART LED EVO MIDDLE 1123MM 5350LM PLX I KL OCHR. ANODA CO IP20 840 (48W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Light source:	LED module	Material of the body:	aluminium
Nominal power [W]:	48	Colour of the body:	CO anode
Rated power of the luminaire [W]:	49.50	Dimensions (H/W/T/S) [mm]:	65/55/1123
Supply voltage [V]:	220-240	Ingress protection:	IP20
Frequency [Hz]:	50 - 60	Mounting version:	suspended
Luminous flux [lm]:	5350	Working temperature [°C]:	from 0 to +25
Luminous efficacy [lm/W]:	108	Net weight [kg]:	1.950
Energy efficiency class:	A+	CE certificate:	35/2017
Electrical protection class:	I	Index:	652486.
Colour temperature [K]:	4000	Category type:	systems
Colour rendering index:	>80	Version:	middle
SDCM:	≤ 3	ETIM class:	EC000282
Power factor:	0.95	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser material:	PMMA	Manual:	Download PDF
Diffuser type:	OPAL		

Card creation date: 17 September 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 35/2017



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl