

SMART LED EVO MIDDLE 1404MM 2250LM PRM I KL OCHR. ANODA CO IP20 830 (20W)

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|-------------------------|-----------|
| Index: | 650550. |
| Ingress protection: | IP20 |
| Luminous flux [lm]*: | 2250 |
| Colour temperature [K]: | 3000 |
| Colour rendering index: | >80 |
| Colour of the body: | C0 anode |
| Diffuser type: | PRM |
| Version: | middle |
| Mounting version: | suspended |

CHARACTERISTICS

The system of a suspended continuous lighting luminaire with a very narrow cross-section. Its body is made of anodized gray aluminum profile. Optical system designed in two variants: opal or prismatic diffuser. The luminaire is equipped with a unique suspension system that facilitates mounting of the luminaire and adjustment of the suspension length.

APPLICATION

Suspended modular continuous lighting system luminaire for internal use. It can used as a primary source of light in offices also when eyesight concentration is required. Unique design, energy-efficient LED panels and the possibility of using DALI systems dedicate the luminaire for use in modern office buildings, with particular emphasis on representative rooms.

SMART LED EVO MIDDLE 1404MM 2250LM PRM I KL OCHR. ANODA CO IP20 830 (20W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|------------|----------------------------|---|
| Light source: | LED module | Material of the body: | aluminium |
| Nominal power [W]: | 20 | Colour of the body: | CO anode |
| Rated power of the luminaire [W]: | 21 | Dimensions (H/W/T/S) [mm]: | 65/55/1404 |
| Supply voltage [V]: | 220-240 | Ingress protection: | IP20 |
| Frequency [Hz]: | 50 - 60 | Mounting version: | suspended |
| Luminous flux [lm]: | 2250 | Working temperature [°C]: | from 0 to +25 |
| Luminous efficacy [lm/W]: | 107 | Net weight [kg]: | 2.370 |
| Energy efficiency class: | A+ | CE certificate: | 35/2017 |
| Electrical protection class: | I | Index: | 650550. |
| Colour temperature [K]: | 3000 | Category type: | systems |
| Colour rendering index: | >80 | Version: | middle |
| SDCM: | ≤ 3 | ETIM class: | EC000282 |
| Power factor: | 0.95 | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Diffuser material: | PMMA | Manual: | Download PDF |
| Diffuser type: | PRM | | |

Card creation date: 17 September 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 35/2017