

SMART LED EVO NT MIDDLE 1123MM 3300LM PRM DALI I KL OCHR. ANODA CO IP20 830 (30W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	648472.
Ingress protection:	IP20
Luminous flux [lm]*:	3300
Colour temperature [K]:	3000
Colour rendering index:	>80
DIMM DALI:	yes
Colour of the body:	C0 anode
Diffuser type:	PRM
Version:	middle
Mounting version:	surface

CHARACTERISTICS

The system of a surface mounted continuous lighting luminaire with a very narrow cross-section. Its body is made of anodized gray aluminum profile. Optical system designed in two variants: opal or prismatic diffuser. The luminaire is equipped with a unique suspension system that facilitates mounting of the luminaire and adjustment of the suspension length.

APPLICATION

Modular continuous lighting system luminaire for internal use. It can be used as a primary source of light in offices also when eyesight concentration is required. Unique design, energy-efficient LED panels and the possibility of using DALI systems dedicate the luminaire for use in modern office buildings, with particular emphasis on representative rooms.

SMART LED EVO NT MIDDLE 1123MM 3300LM PRM DALI I KL OCHR. ANODA CO IP20 830 (30W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Material of the body:	aluminium
Nominal power [W]:	30	Colour of the body:	CO anode
Rated power of the luminaire [W]:	31.60	Dimensions (H/W/T/S) [mm]:	75/55/1123
Supply voltage [V]:	220-240	Ingress protection:	IP20
Frequency [Hz]:	50 - 60	Mounting version:	surface
Luminous flux [lm]:	3300	Working temperature [°C]:	from 0 to +25
Luminous efficacy [lm/W]:	104	DIMM DALI:	yes
Energy efficiency class:	A+	Net weight [kg]:	2.500
Electrical protection class:	I	CE certificate:	35/2017
Colour temperature [K]:	3000	Index:	648472.
Colour rendering index:	>80	Category type:	systems
SDCM:	≤ 3	Version:	middle
Power factor:	0.95	ETIM class:	EC000282
Diffuser material:	PMMA	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser type:	PRM	Manual:	Download PDF

Card creation date: 22 May 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 35/2017



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl