



## TECHNICAL PARAMETERS

---

|                                |                         |
|--------------------------------|-------------------------|
| <b>Index:</b>                  | x                       |
| <b>Ingress protection:</b>     | IP20                    |
| <b>Luminous flux [lm]*:</b>    | 2250 - 5950             |
| <b>Colour temperature [K]:</b> | 3000; 4000              |
| <b>Colour rendering index:</b> | >80                     |
| <b>DIMM DALI:</b>              | yes                     |
| <b>Colour of the body:</b>     | anoda CO; biały; czarny |
| <b>Diffuser type:</b>          | OPAL; PRM               |
| <b>Version:</b>                | end; middle             |
| <b>Mounting version:</b>       | natynkowy; zwieszany    |

## CHARACTERISTICS

---

The system of a surface mounted continuous lighting luminaire with a very narrow cross-section. Its body is made of anodized gray aluminum profile. Optical system designed in two variants: opal or prismatic diffuser. The luminaire is equipped with a unique suspension system that facilitates mounting of the luminaire and adjustment of the suspension length.

## APPLICATION

---

Modular continuous lighting system luminaire for internal use. It can be used as a primary source of light in offices also when eyesight concentration is required. Unique design, energy-efficient LED panels and the possibility of using DALI systems dedicate the luminaire for use in modern office buildings, with particular emphasis on representative rooms.

## DETAILED CARD

### TECHNICAL PARAMETERS TABLE

|                                     |             |                                   |   |
|-------------------------------------|-------------|-----------------------------------|---|
| <b>Light source:</b>                | moduł LED   | <b>Colour of the body:</b>        | anoda C0; biały; czarny   |
| <b>Nominal power [W]:</b>           | 20          | <b>Dimensions (H/W/T/S) [mm]:</b> | 65/55/1123; 65/55/1131;<br>65/55/1404; 65/55/1412;<br>65/55/1420; 75/55/1123;<br>75/55/1131; 75/55/1404 |
| <b>Supply voltage [V]:</b>          | 220-240     | <b>Ingress protection:</b>        | IP20  |
| <b>Frequency [Hz]:</b>              | 50-60       | <b>Mounting version:</b>          | natynkowy; zwieszany  |
| <b>Luminous flux [lm]:</b>          | 2250 - 5950 | <b>Working temperature [°C]:</b>  | od 0 do +25   |
| <b>Energy efficiency class:</b>     | A+; E       | <b>DIMM DALI:</b>                 | yes   |
| <b>Electrical protection class:</b> | I           | <b>Net weight [kg]:</b>           | 1.950; 2.370; 2.470; 2.500  |
| <b>Colour temperature [K]:</b>      | 3000; 4000  | <b>CE certificate:</b>            | 35/2017   |
| <b>Colour rendering index:</b>      | >80         | <b>Index:</b>                     | x   |
| <b>SDCM:</b>                        | ≤ 3         | <b>Category type:</b>             | systems   |
| <b>Power factor:</b>                | 0.91; 0.95  | <b>Version:</b>                   | end; middle   |
| <b>Diffuser material:</b>           | PMMA        | <b>ETIM class:</b>                | EC000282  |
| <b>Diffuser type:</b>               | OPAL; PRM   | <b>Photobiological safety:</b>    | grupa ryzyka 1 (niskie ryzyko)  |
| <b>Material of the body:</b>        | aluminium   | <b>Manual:</b>                    | Pobierz PDF   |

Card creation date: 17 September 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 35/2017



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl