

# SOLEO MIDDLE 1123MM 3200LM PLX I KL OCHR. CZARNY MAT IP20 840 (30W)

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	652417.
Ingress protection:	IP20
Luminous flux [lm]*:	3200
Colour temperature [K]:	4000
Colour rendering index:	>80
Colour of the body:	black
Diffuser type:	OPAL
Version:	middle
Mounting version:	suspended

## CHARACTERISTICS

The system of a suspended continuous lighting luminaire with a very narrow cross-section. Its body is made of anodized gray aluminum profile. Optical system designed in two variants: opal or prismatic diffuser. The luminaire is equipped with a unique suspension system that facilitates mounting of the luminaire and adjustment of the suspension length.

## APPLICATION

Suspended modular continuous lighting system luminaire for internal use. It can used as a primary source of light in offices also when eyesight concentration is required. Unique design, energy-efficient LED panels and the possibility of using DALI systems dedicate the luminaire for use in modern office buildings, with particular emphasis on representative rooms.

# SOLEO MIDDLE 1123MM 3200LM PLX I KL OCHR. CZARNY MAT IP20 840 (30W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Nominal power [W]:	30	Colour rendering index:	>80
Light source:	LED module	SDCM:	≤ 3
Colour temperature [K]:	4000	Power factor:	0.95
Luminous flux [lm]:	3200	Diffuser material:	PMMA
Rated power of the luminaire [W]:	31.60	Material of the body:	aluminium
Diffuser type:	OPAL	Ingress protection:	IP20
Supply voltage [V]:	220-240	Mounting version:	suspended
Frequency [Hz]:	50 - 60	Working temperature [°C]:	from 0 to +25
Version:	middle	Net weight [kg]:	1.950
Colour of the body:	black	CE certificate:	35/2017
Luminous efficacy [lm/W]:	101	Index:	652417.
Dimensions (H/W/T/S) [mm]:	65/55/1123	Category type:	systems
Energy efficiency class:	A+	ETIM class:	EC000282
Electrical protection class:	I	Manual:	Download PDF

Card creation date: 17 September 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 35/2017



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl