# SOLEO NT MIDDLE 1123MM 5500LM PRM I KL OCHR. BIAŁY MAT IP20 830 (48W)

DETAILED CARD

## TECHNICAL PARAMETERS

| | |
|---|---|
| **Index:** | 648540. |
| **Ingress protection:** | IP20 |
| **Luminous flux [lm]*:** | 5500 |
| **Colour temperature [K]:** | 3000 |
| **Colour rendering index:** | >80 |
| **Colour of the body:** | white |
| **Diffuser type:** | PRM |
| **Version:** | middle |
| **Mounting version:** | surface |

## CHARACTERISTICS

The system of a surface mounted continuous lighting luminaire with a very narrow cross-section. Its body is made of anodized gray aluminum profile. Optical system designed in two variants: opal or prismatic diffuser. The luminaire is equipped with a unique suspension system that facilitates mounting of the luminaire and adjustment of the suspension length.

## APPLICATION

Modular continuous lighting system luminaire for internal use. It can used as a primary source of light in offices also when eyesight concentration is required. Unique design, energy-efficient LED panels and the possibility of using DALI systems dedicate the luminaire for use in modern office buildings, with particular emphasis on representative rooms.

# SOLEO NT MIDDLE 1123MM 5500LM PRM I KL OCHR. BIAŁY MAT IP20 830 (48W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

| | | | |
|---|---|---|---|
| **Light source:** | LED module | **Diffuser type:** | PRM |
| **Nominal power [W]:** | 48 | **Material of the body:** | aluminium |
| **Rated power of the luminaire [W]:** | 49.50 | **Colour of the body:** | white |
| **Supply voltage [V]:** | 220-240 | **Dimensions (H/W/T/S) [mm]:** | 75/55/1123 |
| **Frequency [Hz]:** | 50 - 60 | **Ingress protection:** | IP20 |
| **Luminous flux [lm]:** | 5500 | **Mounting version:** | surface |
| **Luminous efficacy [lm/W]:** | 111 | **Working temperature [°C]:** | from 0 to +25 |
| **Energy efficiency class:** | A+ | **Net weight [kg]:** | 1.950 |
| **Electrical protection class:** | I | **CE certificate:** | 35/2017 |
| **Colour temperature [K]:** | 3000 | **Index:** | 648540. |
| **Colour rendering index:** | >80 | **Category type:** | systems |
| **SDCM:** | ≤ 3 | **Version:** | middle |
| **Power factor:** | 0.95 | **ETIM class:** | EC000282 |
| **Diffuser material:** | PMMA | **Manual:** | Download PDF |

Card creation date: 17 September 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 35/2017

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl