

SOLEO END 1131MM 3300LM PRM DALI I KL OCHR. CZARNY MAT IP20 830 (30W)

FICHE DÉTAILLÉE DE PRODUIT



PARAMÈTRES TECHNIQUE

Référence:	652592.
Degré d'étanchéité:	IP20
Flux lumineux du luminaire [lm]*:	3300
Température de couleur [K]:	3000
Indice de rendu des couleurs (Ra):	>80
DIMM DALI:	oui
Couleur du corps:	noir
Type de diffuseur:	PRM
Version:	end
Méthode de montage:	suspendu

CARACTÉRISTIQUES DU PRODUIT

The system of a suspended or surface mounted continuous lighting luminaire with a very narrow cross-section. Its body is made of anodized gray aluminum profile. Optical system designed in two variants: opal or prismatic diffuser. The luminaire is equipped with a unique suspension system that facilitates mounting of the luminaire and adjustment of the suspension length. Characteristics: color temperature 3000K, 4000K; CRI≥80; durability of LED panels 50,000 hours (L70B50) ta = 25°C.

APPLICATION

Suspended modular continuous lighting system luminaire for internal use. It can used as a primary source of light in offices also when eyesight concentration is required. Unique design, energy-efficient LED panels and the possibility of using DALI systems dedicate the luminaire for use in modern office buildings, with particular emphasis on representative rooms.

