

BARIS 40 LED N 5300LM PRM DALI I IP20 1421 MM 840 WHITE 46W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	455209
Rated power of the luminaire [W]*:	46
Luminous flux [lm]*:	5300
Colour temperature [K]:	4000
Ingress protection:	IP20
Energy efficiency class:	D
Material of the body:	aluminium
Colour of the body:	white
Diffuser material:	PC
Diffuser type:	PRM

CHARACTERISTICS

Suspended or surface-mounted luminaire with a very narrow cross-section. The bodies are available as an anodised aluminium profile in grey or as an aluminium profile painted in white or black (other colours available on request). The optical system in the form of an opal cover. The optical system in the form of a prismatic diaphragm reduces glare and is characterized by a greater light transmittance than the opal diffuser, which has a direct impact on a higher value of luminous efficacy. The luminaire is equipped with a unique suspension system that facilitates mounting and adjustment of the suspension length. All BARIS 40 LED suspended luminaires to have 1.2m long slings in a set with a box.

APPLICATION

The luminaire is intended for indoor use. Especially recommended as a source of main lighting conducive to office work. Unique design, energy-saving LED modules and possible integration with external lighting control systems in the DALI standard make this luminaire suitable for use in modern A+ class office buildings, with particular emphasis on representative rooms. Wall lamps are intended, among others for use in corridors, passageways as well as sanitary rooms and bathrooms, where IP44 class is required

BARIS 40 LED N 5300LM PRM DALI I IP20 1421 MM 840 WHITE 46W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	455209	Dimensions (H/W/T/S) [mm]:	53/40/1421
EAN:	4552095905963	Ingress protection:	IP20
Light source:	LED	Mounting dimensions [mm]:	1352
Rated power of the luminaire [W]:	46	DIMM DALI:	1
Colour temperature [K]:	4000	Mounting version:	surface
Luminous flux [lm]:	5300	Net weight [kg]:	1.490
Nominal power [W]:	42	Category type:	battens
Diffuser type:	PRM	AC voltage range [V]:	220 - 240
Frequency [Hz]:	50 - 60	LED lifespan L70B50 [h]:	116000
Luminous efficacy [lm/W]:	115	LED lifespan L80B20 [h]:	73000
Energy efficiency class:	D	LED lifespan L90B10 [h]:	35000
Electrical protection class:	I	Flicker index:	0.060
Colour rendering index:	>80	Impact resistance:	IK03
SDCM:	<3	CE certificate:	236/2023
Power factor:	0.96	ENEC Certificate:	PL BBJ/003/2022
Diffuser material:	PC	PZH certificate:	B-BK-60212-0109/21
Diffuser colour:	transparent	Warranty [years]:	5
Colour of the body:	white	Manual:	Download PDF
Material of the body:	aluminium	Plik LDT:	Pobierz

Card creation date: 08 July 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 236/2023