

# BARIS 40 LED Z 2300LM PRM IIP20 1140 MM 840 ANODE CO 18W

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	454004
<b>Rated power of the luminaire [W]*:</b>	18
<b>Luminous flux [lm]*:</b>	2300
<b>Colour temperature [K]:</b>	4000
<b>Ingress protection:</b>	IP20
<b>Energy efficiency class:</b>	D
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	grey
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	PRM

## CHARACTERISTICS

Suspended or surface-mounted luminaire with a very narrow cross-section. The bodies are available as an anodised aluminium profile in grey or as an aluminium profile painted in white or black (other colours available on request). The optical system in the form of an opal cover. The optical system in the form of a prismatic diaphragm reduces glare and is characterized by a greater light transmittance than the opal diffuser, which has a direct impact on a higher value of luminous efficacy. The luminaire is equipped with a unique suspension system that facilitates mounting and adjustment of the suspension length. All BARIS 40 LED suspended luminaires to have 1.2m long slings in a set with a box.

## APPLICATION

The luminaire is intended for indoor use. Especially recommended as a source of main lighting conducive to office work. Unique design, energy-saving LED modules and possible integration with external lighting control systems in the DALI standard make this luminaire suitable for use in modern A+ class office buildings, with particular emphasis on representative rooms. Wall lamps are intended, among others for use in corridors, passageways as well as sanitary rooms and bathrooms, where IP44 class is required

# BARIS 40 LED Z 2300LM PRM I IP20 1140 MM 840 ANODE CO 18W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	454004	Colour of the body:	grey
EAN:	4540045905963	Dimensions (H/W/T/S) [mm]:	53/40/1140
Light source:	LED	Mounting dimensions [mm]:	1029
Rated power of the luminaire [W]:	18	Ingress protection:	IP20
Nominal power [W]:	16	Mounting version:	suspended
Frequency [Hz]:	50 - 60	Net weight [kg]:	1.360
Luminous flux [lm]:	2300	Category type:	battens
Luminous efficacy [lm/W]:	131	AC voltage range [V]:	220 - 240
Energy efficiency class:	D	LED lifespan L70B50 [h]:	116000
Electrical protection class:	I	LED lifespan L80B20 [h]:	73000
Colour temperature [K]:	4000	LED lifespan L90B10 [h]:	35000
Colour rendering index:	>80	Flicker index:	0.060
SDCM:	<3	Impact resistance:	IK03
Power factor:	0.92	CE certificate:	<a href="#">237/2023</a>
Diffuser material:	PC	ENEC Certificate:	<a href="#">PL BBJ/003/2022</a>
Diffuser type:	PRM	PZH certificate:	<a href="#">B-BK-60212-0109/21</a>
Diffuser colour:	transparent	Warranty [years]:	5
Material of the body:	aluminium	Manual:	<a href="#">Download PDF</a>

## LIGHT CURVES



Card creation date: 08 July 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 237/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl