

# BARIS 40 LED Z 5900LM PRM IIP44 1140 MM 840 ANODE CO 50W

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	454486
<b>Rated power of the luminaire [W]*:</b>	50
<b>Luminous flux [lm]*:</b>	5900
<b>Colour temperature [K]:</b>	4000
<b>Ingress protection:</b>	IP44
<b>Energy efficiency class:</b>	D
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	grey
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	PRM

## CHARACTERISTICS

Suspended or surface-mounted luminaire with a very narrow cross-section. The bodies are available as an anodised aluminium profile in grey or as an aluminium profile painted in white or black (other colours available on request). The optical system in the form of an opal cover. The optical system in the form of a prismatic diaphragm reduces glare and is characterized by a greater light transmittance than the opal diffuser, which has a direct impact on a higher value of luminous efficacy. The luminaire is equipped with a unique suspension system that facilitates mounting and adjustment of the suspension length. All BARIS 40 LED suspended luminaires to have 1.2m long slings in a set with a box.

## APPLICATION

The luminaire is intended for indoor use. Especially recommended as a source of main lighting conducive to office work. Unique design, energy-saving LED modules and possible integration with external lighting control systems in the DALI standard make this luminaire suitable for use in modern A+ class office buildings, with particular emphasis on representative rooms. Wall lamps are intended, among others for use in corridors, passageways as well as sanitary rooms and bathrooms, where IP44 class is required

# BARIS 40 LED Z 5900LM PRM IIP44 1140 MM 840 ANODE CO 50W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	454486
EAN:	4544865905963
Light source:	LED
Rated power of the luminaire [W]:	50
Colour temperature [K]:	4000
Luminous flux [lm]:	5900
Nominal power [W]:	47
Diffuser type:	PRM
Frequency [Hz]:	50 - 60
Luminous efficacy [lm/W]:	117
Energy efficiency class:	D
Electrical protection class:	I
Colour rendering index:	>80
SDCM:	<3
Power factor:	0.97
Diffuser material:	PC
Diffuser colour:	transparent
Colour of the body:	grey
Material of the body:	aluminium

Dimensions (H/W/T/S) [mm]:	53/40/1140
Ingress protection:	IP44
Mounting dimensions [mm]:	1029
Mounting version:	suspended
Net weight [kg]:	1.480
Category type:	battens
AC voltage range [V]:	220 - 240
LED lifespan L70B50 [h]:	109000
LED lifespan L80B20 [h]:	69000
LED lifespan L90B10 [h]:	34000
Flicker index:	0.060
Impact resistance:	IK03
CE certificate:	<a href="#">237/2023</a>
ENEC Certificate:	<a href="#">PL BBJ/004/2022</a>
PZH certificate:	<a href="#">B-BK-60212-0109/21</a>
Warranty [years]:	5
Manual:	<a href="#">Download PDF</a>
Plik LDT:	<a href="#">Pobierz</a>

Card creation date: 08 July 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 237/2023