

# BARIS 40 LED N VD 1350LM PRM I IP20 579 MM 840 BLACK 15W

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	455407
<b>Rated power of the luminaire [W]*:</b>	15
<b>Luminous flux [lm]*:</b>	1350
<b>Colour temperature [K]:</b>	4000
<b>Ingress protection:</b>	IP20
<b>Energy efficiency class:</b>	F
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	black
<b>Diffuser type:</b>	PRM
<b>Mounting version:</b>	surface

## CHARACTERISTICS

Suspended or surface-mounted luminaire with a very narrow cross-section. The bodies are available as an anodised aluminium profile in grey or as an aluminium profile painted in white or black (other colours available on request). Optical system in the form of an opal cover. The luminaire is equipped with a unique suspension system that facilitates mounting and adjustment of the suspension length. All suspended BARIS LED VD luminaires have slings with a box included in the set.

## APPLICATION

The luminaire is intended for indoor use. Unique design, energy-saving LED modules, and possible integration with external lighting control systems in the DALI standard make this luminaire suitable for use in modern office buildings, with particular emphasis on representative rooms.

Versions marked "VD" are only intended for use in traffic zones and corridors inside buildings included in Table 5.1 of EN12464.

# BARIS 40 LED N VD 1350LM PRM I IP20 579 MM 840 BLACK 15W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	455407	Dimensions (H/W/T/S) [mm]:	53/40/579
EAN:	4554075905963	Ingress protection:	IP20
Rated power of the luminaire [W]:	15	Mounting dimensions [mm]:	510
Light source:	LED	Mounting version:	surface
Colour temperature [K]:	4000	Net weight [kg]:	0.510
Frequency [Hz]:	50	Category type:	battens
Luminous flux [lm]:	1350	AC voltage range [V]:	220 - 240
Diffuser type:	PRM	LED lifespan L70B50 [h]:	113500
Energy efficiency class:	F	LED lifespan L80B20 [h]:	71500
Nominal power [W]:	13	LED lifespan L90B10 [h]:	34500
Luminous efficacy [lm/W]:	88	Flicker index:	0.060
Electrical protection class:	I	CE certificate:	<a href="#">307/2023</a>
Colour rendering index:	>80	ENEC Certificate:	<a href="#">PL BBJ/003/2022</a>
SDCM:	<3	PZH certificate:	<a href="#">B-BK-60212-0109/21</a>
Diffuser material:	PS	Warranty [years]:	3
Diffuser colour:	transparent	Manual:	<a href="#">Download PDF</a>
Colour of the body:	black	Impact resistance:	IK03
Material of the body:	aluminium		

## LIGHT CURVES



Card creation date: 09 July 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 307/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl