

# SQ 600 LED 10900LM PRM RCR I KL. IP20 592X592MM 840 (73W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	668838
<b>Ingress protection:</b>	IP44/IP20
<b>Nominal power [W]:</b>	73
<b>Luminous flux [lm]*:</b>	10900
<b>Colour rendering index:</b>	>80
<b>SDCM:</b>	≤ 3
<b>Energy efficiency class:</b>	C
<b>Material of the body:</b>	ABS
<b>Diffuser material:</b>	PS
<b>Diffuser type:</b>	PRM

## CHARACTERISTICS

SQ 600 LED is a new line of square luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

The luminaire is available in 2 versions:

- with OPAL diffuser - providing soft light;
- with PRM diffuser - with higher luminous efficiency and low glare UGR <19 (18W, 24W, 32W versions).

Available options:

- RCR sensor - sensor used for motion detection, without twilight detection option; uses microwaves for detection (active sensor),
- control in the DALI standard,
- CORRIDOR corridor function (RCR + DALI).

The ingress protection- depends on the method of installation:

- surface mounted - IP20,
- flush-mounted - IP44/20.

## APPLICATION

Surface-mounted luminaire with the possibility of flush mounting in modular ceilings and in plasterboard ceilings (using plasterboard recessing kit) is especially recommended for offices, spacious corridors and public spaces.


# SQ 600 LED 10900LM PRM RCR I KL. IP20 592X592MM 840 (73W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	668838	Ingress protection:	IP44/IP20
Light source:	LED module	Glow wire test [°C]:	650
Nominal power [W]:	73	Mounting version:	surface mounted; recessed mounted in modular ceiling possible
Rated power of the luminaire [W]:	75	Motion sensor:	yes
Supply voltage [V]:	220 - 240	Net weight [kg]:	62
Frequency [Hz]:	50 - 60	Category type:	louvres
Luminous flux [lm]:	10900	Category of application:	commercial facilities, educational institutions
Luminous efficacy [lm/W]:	145	AC voltage range [V]:	198 – 264
Energy efficiency class:	C	DC voltage range [V]:	176 – 280
Electrical protection class:	I	LED lifespan L70B50 [h]:	98000
Colour temperature [K]:	4000	LED lifespan L80B20 [h]:	62000
Colour rendering index:	>80	LED lifespan L90B10 [h]:	30000
SDCM:	≤ 3	Light distribution type:	open space
Power factor:	0.95	EAN:	6688385905963
Diffuser material:	PS	Plug type:	80W/150-350mA 120-350VDC HELVAR LL 1x23-80-E-CC
Diffuser type:	PRM	PZH certificate:	<a href="#">B-BK-60212-0618/20</a>
Diffuser colour:	transparent	Version:	FR4
Material of the body:	ABS	Dusk sensor:	yes
Colour of the body:	white	CE certificate:	<a href="#">110/2023</a>
Dimensions (H/W/T/S) [mm]:	592/592/44	Manual:	<a href="#">Download PDF</a>
Mounting dimensions [mm]:	563/297	ENEC Certificate:	<a href="#">PL BBJ/006/2021/M1</a>

## LIGHT CURVES



# SQ 600 LED 10900LM PRM RCR I KL. IP20 592X592MM 840 (73W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
999543	Plasterboard recessing kit 630x630 white (steel version)
978395	Installation kit SQ 600 Ceiling system H40 100x100
374845	Frame adapter KG 635x635 WHITE
998966	Frame steel white structure RAL9016 600x600 SM "well effect"



Plasterboard recessing kit 630x630 white (steel version) (999543)



Frame steel white structure RAL9016 600x600 SM "well effect" (998966)

Card creation date: 19 August 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 110/2023