EXPO SYSTEM LED FI 85 1700LM 24ST I KL IP20 CZARNY 830 (18W)

DETAILED CARD





TECHNICAL PARAMETERS

Index:	254307
Ingress protection:	IP20
Nominal power [W]:	18
Luminous flux [lm]*:	1700
Colour temperature [K]:	3000
Electrical protection class:	1
Energy efficiency class:	F
Colour of the body:	black
Diffuser type:	lens
Beam angle [°]:	24

CHARACTERISTICS

High quality aluminum projector with LED COB light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability. Immediate ignition without flicker makes it the best replacement for metal halide or halogen sources projectors. Optional specialized filters to highlight meat stands, bread or vegetables. Version CRi (Ra)> 90 available on request.

APPLICATION

Possible use of specialized filters to highlight food stands. As accentuating lighting in commercial buildings, museums, exhibition halls and offices. For connection with track systems in the color of the projector




TECHNICAL PARAMETERS TABLE

Light source:	LED module
Nominal power [W]:	18
Rated power of the luminaire [W]:	19.80
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [Im]:	1700
Luminous efficacy [lm/W]:	85
Energy efficiency class:	F
Electrical protection class:	1
Colour temperature [K]:	3000
Colour rendering index:	80
Beam angle [°]:	24
Diffuser material:	PMMA
Diffuser type:	lens
Material of the body:	aluminium
Colour of the body:	black

Dimensions (H/W/T/S) [mm]:	Ø85/255mm	
Ingress protection:	IP20	
Mounting version:	track, surface	
Working temperature [°C]:	from -20 to +35	
Tilt angle adjustment [°]:	355	
Net weight [kg]:	1.100	
CE certificate:	<u>45/2020</u>	
Index:	254307	
EAN:	5905963254307	
Category type:	spotlight	
ETIM class:	EC001744	
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)	
Warranty [years]:	2	
Manual:	Download PDF	
Plik LDT:	Download	

LIGHT CURVES





ACCESSORIES AVAILABLE

index	Name
255106	EXPO SYSTEM LED surface mounting base black
255113	EXPO SYSTEM LED surface mounting base white
255120	EXPO SYSTEM LED honeycomb



EXPO SYSTEM LED surface mounting base black (255106)



EXPO SYSTEM LED surface mounting base white (255113)



EXPO SYSTEM LED honeycomb (255120)

