



TECHNICAL PARAMETERS

Index:	254314
Ingress protection:	IP20
Nominal power [W]:	18
Luminous flux [lm]*:	1750
Colour temperature [K]:	3000
Electrical protection class:	I
Energy efficiency class:	F
Colour of the body:	black
Diffuser type:	lens
Beam angle [°]:	36

CHARACTERISTICS

High quality aluminum projector with LED COB light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability. Immediate ignition without flicker makes it the best replacement for metal halide or halogen sources projectors. Optional specialized filters to highlight meat stands, bread or vegetables. Version CRI (Ra)> 90 available on request.

APPLICATION


Possible use of specialized filters to highlight food stands. As accentuating lighting in commercial buildings, museums, exhibition halls and offices. For connection with track systems in the color of the projector

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Dimensions (H/W/T/S) [mm]:	Ø85/255mm
Nominal power [W]:	18	Ingress protection:	IP20
Rated power of the luminaire [W]:	19.80	Mounting version:	track, surface
Supply voltage [V]:	220-240	Working temperature [°C]:	from -20 to +35
Frequency [Hz]:	50 - 60	Tilt angle adjustment [°]:	355
Luminous flux [lm]:	1750	Net weight [kg]:	1.100
Luminous efficacy [lm/W]:	88	CE certificate:	45/2020
Energy efficiency class:	F	Index:	254314
Electrical protection class:	I	EAN:	5905963254314
Colour temperature [K]:	3000	Category type:	spotlight
Colour rendering index:	80	ETIM class:	EC001744
Beam angle [°]:	36	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser material:	PMMA	Warranty [years]:	2
Diffuser type:	lens	Manual:	Download PDF
Material of the body:	aluminium	Plik LDT:	Download
Colour of the body:	black		

LIGHT CURVES



DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
255106	EXPO SYSTEM LED surface mounting base black
255113	EXPO SYSTEM LED surface mounting base white
255120	EXPO SYSTEM LED honeycomb



EXPO SYSTEM LED surface mounting base black (255106)



EXPO SYSTEM LED surface mounting base white (255113)



EXPO SYSTEM LED honeycomb (255120)